

# WATER SUPPLY CONNECTORS



Meeting the demands of the Pro, Fluidmaster® has added new professional-grade faucet and toilet connectors to the Fluidmaster PRO Series™ line. This new line features 18 of the most popular braided stainless steel connectors with No-Burst® technology. Backed by a 10-year warranty, for professional installation only.



## TOILET



- No-Burst® braided stainless steel
- Lengths range from 9" to 20"
- Ample inside diameter for high flow capacity
- Won't kink or crease, even in the tightest of spaces
- Exceeds all requirements for flexible water connectors as defined by ASME A112.18.6 and CSA B125
- 10-year warranty



## FAUCET



- No-Burst® braided stainless steel
- Lengths range from 12" to 30"
- Ample inside diameter for high flow capacity
- Won't kink or crease, even in the tightest of spaces
- Exceeds all requirements for flexible water connectors as defined by ASME A112.18.6 and CSA B125
- 10-year warranty

TOILET

| MODEL NUMBER | UPC 0 39961 | CONNECTOR CONFIGURATION   | PACK QTY | CASE DIMENSIONS W/D/H INCHES | CUBIC FEET | CASE WEIGHT | SCC 1 2 OF 5 100 39961 |
|--------------|-------------|---|----------|------------------------------|------------|-------------|------------------------|
| PRO1T09      | 10011 5     | 3/8" Female Compression Thread<br>X 7/8" Female Ballcock Thread   | 25       | 6.75 x 9.75 x 5.00           | 0.20       | 5.00        | 10011 2                |
| PRO1T12      | 10013 9     |   | 25       | 6.75 x 13.75 x 5.00          | 0.27       | 6.00        | 10013 6                |
| PRO1T20      | 10014 6     |   | 25       | 8.25 x 16.75 x 5.00          | 0.40       | 8.00        | 10014 3                |
| PRO4T09      | 10021 4     | 1/2" I.P. Female Straight Thread<br>X 7/8" Female Ballcock Thread | 25       | 6.75 x 9.75 x 5.00           | 0.20       | 5.00        | 10021 1                |
| PRO4T12      | 10022 1     |   | 25       | 6.75 x 13.75 x 5.00          | 0.27       | 6.00        | 10022 8                |
| PRO4T20      | 10023 8     |   | 25       | 8.25 x 16.75 x 5.00          | 0.40       | 8.00        | 10023 5                |

FAUCET

|         |         |  |    |                     |      |       |         |
|---------|---------|--|----|---------------------|------|-------|---------|
| PRO1F12 | 10012 2 | 3/8" Female Compression Thread<br>X 1/2" I.P. Female Straight Thread   | 25 | 6.75 x 13.75 x 5.00 | 0.27 | 6.00  | 10012 9 |
| PRO1F16 | 10016 0 |  | 25 | 8.25 x 16.75 x 5.00 | 0.40 | 7.00  | 10016 7 |
| PRO1F20 | 10020 7 |  | 25 | 8.25 x 16.75 x 5.00 | 0.40 | 8.00  | 10020 4 |
| PRO1F30 | 10030 6 |  | 25 | 8.25 x 16.75 x 5.00 | 0.40 | 10.00 | 10030 3 |
| PRO4F12 | 10015 3 | 1/2" I.P. Female Straight Thread<br>X 1/2" I.P. Female Straight Thread | 25 | 6.75 x 13.75 x 5.00 | 0.27 | 7.00  | 10015 0 |
| PRO4F16 | 10017 7 |  | 25 | 8.25 x 16.75 x 5.00 | 0.40 | 8.00  | 10017 4 |
| PRO4F20 | 10018 4 |  | 25 | 8.25 x 16.75 x 5.00 | 0.40 | 8.00  | 10018 1 |
| PRO4F30 | 10019 1 |  | 25 | 8.25 x 16.75 x 5.00 | 0.40 | 11.00 | 10019 8 |
| PRO6F12 | 10024 5 | 3/8" Female Compression<br>X 3/8" Female Compression                   | 25 | 6.75 x 13.75 x 5.00 | 0.27 | 6.00  | 10024 2 |
| PRO6F20 | 10025 2 |  | 25 | 8.25 x 16.75 x 5.00 | 0.40 | 7.00  | 10025 9 |
| PRO8F12 | 10026 9 | 3/8" Female Compression Thread<br>X 3/8" O.D. Copper Tubing Coupling   | 25 | 6.75 x 13.75 x 5.00 | 0.27 | 6.00  | 10026 6 |
| PRO8F20 | 10027 6 |  | 25 | 8.25 x 16.75 x 5.00 | 0.40 | 8.00  | 10027 3 |