



Pump Tanks - Sourceline™



INLINE MODELS

- Appliance Gray finish
- Maximum working temperature: 200 °F.
- Maximum working pressure: 100 PSIG



ANSI/NSF 61



Part Number	Dimensions (ins)		Total Volume (gal)	Max Accept Factor	Drawdown (gal)			Shipping Wt (Vol) lbs (cu ft)	Pallet Qty	System Conn. NPTM	Precharge Pressure (psig)	List Price
	Dia	Height			20/40	30/50	40/60					
SL2I	8	12 5/8	2.0	0.45	0.8	0.7	0.6	5 (0.6)	75	3/4"	20	\$ 92.90
SL4I	11	15	4.4	0.55	1.8	1.5	1.3	9 (1.2)	48	3/4"	20	127.10
SL8I	11	22 13/16	7.6	0.37	3.1	2.6	2.2	15 (2.0)	32	3/4"	30	206.40
SL10I	15 3/8	17 3/4	10.3	1.00	4.1	3.5	3.0	20 (2.6)	18	1"*	38	230.80
SL14I	15 3/8	22	14.0	0.81	5.6	4.8	4.1	22 (3.3)	18	1"*	38	245.50

* NPTF connection.



VERTICAL STAND MODELS

- Appliance Gray finish
- Malleable elbow system connection.
- Maximum working temperature: 200 °F.



ANSI/NSF 61

Part Number	Dimensions (ins)		Total Volume (gal)	Max Accept Factor	Drawdown (gal)			Shipping Wt (Vol) lbs (cu ft)	Pallet Qty	System Conn. NPTF	Precharge Pressure (PSIG)	Max WP (PSIG)	List Price
	Dia	Height			20/40	30/50	40/60						
SL10V	15 3/8	19 1/4	10.3	1.00	4.1	3.5	3.0	23 (3.0)	18	1"	38	100	\$ 301.70
SL14V	15 3/8	23 7/8	14.0	0.81	5.6	4.8	4.1	25 (3.8)	18	1"	38	100	301.70
SL20V	15 3/8	31 5/8	20.0	0.57	8.0	6.8	5.9	33 (4.9)	18	1"	38	100	260.10
SL32V	15 3/8	45	32.0	0.35	-	10.9	9.4	43 (7.0)	9	1"	38	100	444.50
SL34V	22	29 5/8	34.0	1.00	13.7	11.6	10.0	61 (9.5)	4	1 1/4"	38	100	487.30
SL44V	22	36	44.0	0.77	17.7	15.0	13.0	69 (11.0)	4	1 1/4"	38	125	563.10
SL62V	22	46 3/4	62.0	0.55	24.9	21.1	18.3	92 (13.9)	4	1 1/4"	38	125	665.60
SL86VT	22	62 1/4	86.0	0.39	34.6	29.2	25.4	114 (18.1)	4	1 1/4"	38	100	856.60
SL86VS	26	47 1/4	86.0	0.54	34.6	29.2	25.4	123 (18.9)	4	1 1/4"	38	125	790.10
SL119V	26	61 7/8	119.0	0.39	47.8	40.5	35.1	166 (24.5)	4	1 1/4"	38	125	1125.80



HORIZONTAL PUMP STAND MODELS

- Appliance Gray finish
- Maximum working temperature: 200 °F.
- Maximum working pressure: 100 PSIG



ANSI/NSF 61

Part Number	Dimensions (ins)			Total Volume (gal)	Max Accept Factor	Drawdown (gal)			Shipping Wt (Vol) lbs (cu ft)	Pallet Qty	System Conn. NPTM	Precharge Pressure (psig)	List Price
	H	W	L			20/40	30/50	40/60					
SL5H	11	10 1/2	18 1/4	5.3	0.80	2.1	1.8	1.6	13 (1.5)	72	3/4"	20	\$ 178.30
SL14H	16	15 3/8	20 7/8	14.0	0.81	5.6	4.8	4.1	29 (4.0)	18	1"	38	310.20



American Granby Inc.™

In the United States:
In Canada:

Phone (800) 776-2266
Phone (866) 503-5523

www.americangranby.com
Fax (800) 729-3299
Fax (888) 562-2095

6/04 V2