

SPF MALLEABLE IRON FITTINGS

Class 150 (Standard)


STANDARDS & SPECIFICATIONS

Import Malleable Iron Screwed Fittings (Class 150)

Dimensional:	Fittings:	ASME B16.3	
	Unions:	ASME B 16.39	
	Bushings/Plugs:	ASME B 16.14	
Material:	ASTM A-197		
Galvanizing:	ASTM A-153	(Hot Dip Galvanizing)	
Threading:*	ASME B 1.20.1		
Pressure Rating:	Fittings:	ASME B 16.3	
	Unions:	ASME B 16.39	
	Bushings/Plugs:	ASME B 16.14	
Pressure Testing:	All malleable iron fittings are tested for through wall porosity using an air under water process.		
Agency Approvals:	All malleable iron fittings and unions are UL Listed and FM Approved.		

*British Standard threading per BS 21 available upon request.

90° REDUCING ELBOW



Size	A	B	Weight
in	in	in	lbs
1/4 x 1/8	0.74	0.76	0.08
3/8 x 1/8	0.81	0.85	0.11
3/8 x 1/4	0.88	0.90	0.13
1/2 x 1/4	0.97	0.98	0.16
1/2 x 3/8	1.04	1.03	0.19
3/4 x 3/8	1.12	1.13	0.26
3/4 x 1/2	1.20	1.22	0.29
1 x 3/8	1.18	1.26	0.35
1 x 1/2	1.26	1.36	0.42
1 x 3/4	1.37	1.45	0.47
1 1/4 x 1/2	1.34	1.53	0.54
1 1/4 x 3/4	1.45	1.62	0.62
1 1/4 x 1	1.58	1.67	0.73
1 1/2 x 1/2	1.38	1.65	0.65
1 1/2 x 3/4	1.52	1.75	0.74
1 1/2 x 1	1.65	1.80	0.88
1 1/2 x 1 1/4	1.82	1.88	1.03
2 x 1/2	1.50	1.89	0.93
2 x 3/4	1.60	1.97	1.04
2 x 1	1.73	2.02	1.28
2 x 1 1/4	1.90	2.10	1.36
2 x 1 1/2	2.02	2.16	1.51
2 1/2 x 1 1/2	2.16	2.51	2.20
2 1/2 x 2	2.39	2.60	2.55
3 x 2	2.52	2.89	3.35
3 x 2 1/2	2.83	2.99	4.12
4 x 2	2.72	3.43	5.01
4 x 3	3.30	3.60	6.65