

## Specifications

### Materials

All exposed materials are stainless steel or chrome-plated brass. Valve bodies are cast brass.

### Standard Equipment

#### In Wall Shower Valve as Selected

For more detailed information refer to tech data for specific valve.

### Supply Inlets

Female supply inlets are 1/2"

### Optional Equipment

#### Showerhead—1/2" NPT

Institutional or deluxe type chrome-plated showerhead with bent arm and flange or wall arm.

### Flow Control

A 2.0 GPM flow control is standard (actual flow may vary but will not exceed 2.5 GPM max.)

### Hand-Held Shower Spray

Constructed with a 60" stainless steel flexible hose and post style mounting bracket for wall mount or slide bar. Elevated in-line back flow preventer with or without quick disconnect for flexible hose.

### Diverter Valve

Lever handle operation for easy transfer of water flow between fixed and hand held spray.

### Tub Spout

Diverter type spout with 1/2" inlet.

### Sample Specification

Built-in shower shall be Bradley Model 1C-EF/S. Built-in shower with Equa-Flo pressure balancing valve, and vandal-proof institutional showerhead (S).

Model	Description
<input checked="" type="checkbox"/> 1C	Built-In Showers with Concealed Supplies

### Required Selections (Must select one from each category)

#### Valves (select one):

##### Hot/tempered and cold supplies

- ☐ EF Equa-Flo Pressure-Balancing Valve
- ☐ C5 Equa-Flo C5 Pressure-Balancing Valve
- ☐ HD Equa-Flo HD Pressure-Balancing Valve
- ☐ TMV Thermostatic Mixing Valve
- ☐ HC Hot and Cold Compression Valve

##### Single tempered/cold supply

- ☐ AZ\* Infrared Metering Valve
- ☐ AST Air Metering Valve
- ☐ PM Presto 50B Metering Valve
- ☐ SV Single Compression Valve
- ☐ SVL Single Compression Valve with Lever Handle
- ☐ TT\* TouchTime® Metering Valve — 1 minute
- ☐ TT3\* TouchTime® Metering Valve — 3 minutes

\*AZ, TT, and TT3 valves require optional 24V Class 2 transformers, available as a separate item from Bradley



### Optional Selections

#### Showerhead w/ Bent Arm and Flange:

- ☐ S1 Standard Institutional Showerhead
- ☐ D1 Deluxe Showerhead w/ Ball Joint
- ☐ B1 Brass Showerhead w/ Ball Joint
- ☐ E1 Economy Soft Flow Showerhead
- ☐ J1 Multi-Jet Chrome-Plated Brass Showerhead

#### Showerhead w/ Wall Arm:

- ☐ S Standard Institutional Showerhead
- ☐ SF Deluxe Showerhead w/ Ball Joint
- ☐ BS Brass Showerhead w/ Ball Joint
- ☐ ES Economy Soft Flow Showerhead
- ☐ SX Severe Service Showerhead

#### Optional Flow Control (available with S, SX and S1 only):

- ☐ G 1.5 GPM Flow Control

#### Showerhead Options (not available with SX, E1, J1, B1, BS or ES):

- ☐ AKV Allen Key Volume Control
- ☐ LBJ Lockable Ball Joint
- ☐ THV T-Handle Volume Control

#### Hand Shower Variations:

- ☐ B24 With 60" Flexible Hose, 24" Metal Slide Bar and Vacuum Breaker
- ☐ E24 With 60" Flexible Hose, 24" Economy Slide Bar and Vacuum Breaker
- ☐ SB With 60" Flexible Hose, 24" Metal Slide Bar, Vacuum Breaker and Quick Disconnect
- ☐ HW With 60" Flexible Hose, Wall Hooks and Vacuum Breaker
- ☐ HS With 60" Flexible Hose, Wall Hooks, Vacuum Breaker and Quick Disconnect

#### Diverter Valve:

- ☐ DV In-Wall Diverter Valve

#### Tub Spout:

- ☐ TS Tub Spout — threaded
- ☐ DJ Tub Spout — slip joint

#### Supply Stops (included with EF, HD and TMV valves):

- ☐ ST Stops in Supply for Valves
- ☐ DC Deduct Checkstops (provided standard w/ EF, HD and TMV)

#### Miscellaneous:

- ☐ AP Anchor Plate for Showerhead
- ☐ SD Wall Mounted Soap Dish
- ☐ BP Back Plate for Showerhead
- ☐ RSD Recessed Soap Dish