

HC

Number of Stations: **6, 12**
Expands up to 36 stations
Wi-Fi Enabled

FEATURES

- 6 and 12 station standard controllers
- Wi-Fi enabled for simple connection to the internet
- Schedule adjustment based on local weather
- 12 station expansion module allows for expansion to 36 stations
- Watering overflow detection and alerts
- Wiring fault detection and alerts
- Flow meter measures water usage and leak detection
- Warranty: 2 years

ELECTRICAL SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC (international model)
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- Pump/master valve (24 VAC): 0.28 A
- Sensor inputs: 2
- Operating temperature: 0°F to 140°F

APPROVALS

- CE, C-tick, FCC

► = *Advanced Feature descriptions on pages 83*

* Hydrowise software information on page 104



Plastic Indoor

Height: 6"
 Width: 7"
 Depth: 1.3"



Flow Meter - ¾" coupling

Height: 5.1"
 Length: 9.1"
 Depth: 3.1"

Flow Meter - 1" coupling

Height: 6.3"
 Length: 9.1"
 Depth: 3.1"



Compatible with Hydrowise software

HC - OPTIONS

Models	Description
HC-1200M	12 station expansion module
HC-075-FLOW	Flow meter with ¾" NPT thread
HC-100-FLOW	Flow meter with 1" NPT thread

HC - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Models	2 Transformer	3 Indoor/Outdoor	4 Options
HC-6 = 6 station controller with Wi-Fi connection HC-12 = 12 station indoor controller with Wi-Fi connection	00 = 120 VAC	i = Indoor model	(Blank) = No option E = 230 VAC with European connections A = 230 VAC with Australian connections <i>(outdoor model has internal transformer with cord)</i>

Examples:

HC-600i-A = 6-Station 230 VAC indoor plastic controller, and with Australian cord

HC-1200i-E = 12-Station 120 VAC indoor plastic controller, and with European cord