


NDS STANDARD SERIES VALVE BOXES – RESIDENTIAL/COMMERCIAL GRADE

NDS Standard Series 13" x 20" Jumbo Rectangular Valve Boxes


Specifications: The NDS STANDARD SERIES 13" x 20" body is tapered and has a minimum wall thickness of 0.250". The body has a double wall at the top cover seat area with a minimum thickness of 0.250". The cover seat area has 16 structural support ribs on the underside of the seat, each with a minimum thickness of 0.250". The bottom of the body has a 0.500" flange. The 13" x 20" cover has an average thickness of 0.250". The valve box has a 3/8" 304 SS nut for the bolt-down as a standard feature.



Part No.	Description - Marking	Color (Box/Cover)	Pallet Qty.	Wt. Ea. lbs.	Product Class
Box & Cover					
117BC	13" x 20" Jumbo Box, Overlapping Cover - ICV	Black/Green	56	14.00	20ND
117BC SAND	13" x 20" Jumbo Box, Overlapping Cover - ICV	Sand/Sand	56	14.00	20ND
117BCS	13" x 20" Jumbo Box, Overlapping Cover - Sewer	Black/Green	56	14.00	20NM
118BC	Jumbo Box and Cover	Green/Green	56	14.00	20ND
118TBC	12" x 20" x 6" Tapered Box and Cover	Green/Green	56	14.00	20ND
119	13" x 20" x 6" Jumbo Extension, Overlapping Cover - ICV	Black/Green	32	12.00	20ND
119TBC	13" x 20" x 6" Tapered Box, Overlapping Cover - ICV	Black/Green	56	12.00	20ND
119 SAND	13" x 20" x 6" Jumbo Extension, Overlapping Cover - ICV	Sand/Sand	32	12.00	20ND
Cover Only					
117C	13" x 20" Overlapping Cover - ICV	Green	180	5.00	20ND
117CD	Jumbo Box ICV Cover	Green	180	1.30	20ND
117C SAND	13" x 20" Overlapping Cover - ICV	Sand	180	5.00	20ND
117CS	13" x 20" Jumbo Overlapping Cover - Sewer	Green	180	5.00	20NM
Box Only					
117B	13" x 20" Jumbo Box	Black	56	9.00	20NM
117-6	13" x 20" x 6" Jumbo Extension	Black	32	6.00	20ND
118TB	12" x 20" x 6" Tapered Box	Green	56	6.15	20ND
119TB	13" x 20" x 6" Tapered Box	Black	56	6.00	20ND
113BB	2-1/2" x 3/8" SS Bolt	Steel	(Bag of 10)	0.10	20NM

NDS Standard Series 13" x 24" Rectangular Valve Boxes

Specifications: The NDS STANDARD SERIES 13" x 24" body is tapered and has a minimum wall thickness of 0.270". The body has a double wall at the top cover seat area with a minimum thickness of 0.270". The cover seat area has 18 structural support ribs on the underside of the seat, each with a minimum thickness of 0.250". The bottom of the body has a 1.000" flange. The 13" x 24" cover has an average thickness of 0.320". The valve box has a 3/8" 304 SS nut for the bolt-down as a standard feature.



Part No.	Description - Marking	Color (Box/Cover)	Pallet Qty.	Wt. Ea. lbs.	Product Class
Box & Cover					
121BCB	13" x 24" x 12" Box, Overlapping Bolt-Down Cover - ICV	Black/Green	12	24.00	20ND
125BCB	13" x 24" x 15" Box, Overlapping Bolt-Down Cover - ICV	Black/Green	12	26.00	20ND
121BCDB	13" x 24" x 12" Box, Drop-in Bolt-Down Cover - ICV	Black/Green	12	24.00	20ND
125BCDB	13" x 24" x 15" Box, Drop-in Bolt-Down Cover - ICV	Black/Green	12	26.00	20ND
125PBCRB	13" x 24" x 15" Box, Overlapping Cover - Reclaimed Water	Black/Purple	12	26.00	20ND
Cover Only					
121CR	13" x 24" Overlapping Reclaimed Cover	Purple	125	7.00	20ND
222C	13" x 24" Overlapping Cover - ICV	Green	125	7.00	20PR
Box Only					
125B	13" x 24" x 15" Box	Black	12	19.00	20NM