

# PRO-HC

Number of Stations: **6, 12, 24**  
Type: **Fixed**

## FEATURES

- Indoor and outdoor models
- Full-functioning controller with touchscreen
- Wi-Fi enabled for simple and fast connection to the internet
- 6, 12 and 24 fixed station controllers
- Dedicated master valve/pump start
- Large terminal strips and wiring compartment
- Built-in milliamp sensor across the full range of controllers
- Warranty period: 2 years
- ▶ Touchscreen Interface
- ▶ Predictive Water™ Adjustments
- ▶ Flow Meter Detection and Alerts
- ▶ Wiring Detection and Alerts
- ▶ Advanced Sensor Ports

## ELECTRICAL SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC (international model)
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV: (24 VAC): 0.28 A
- Sensor inputs: 2
- Operating temperature: 0° F to 140° F

## APPROVALS

- CE, UL, cUL, C-tick, FCC

HC - OPTIONS	
Models	Description
<b>HC-075-FLOW</b>	Flow meter with ¾" NPT thread
<b>HC-100-FLOW</b>	Flow meter with 1" NPT thread



### Plastic Indoor

Height: 8.25"  
Width: 9.5"  
Depth: 3.5"

### Plastic Outdoor

Height: 9"  
Width: 10"  
Depth: 4"



### HC Flow Meter - ¾" thread

Height: 5.1"  
Length: 9.1"  
Depth: 3.1"

### HC Flow Meter - 1" thread

Height: 6.3"  
Length: 9.1"  
Depth: 3.1"



Compatible with Hydrawise software

## PRO-HC - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Transformer	3 Indoor/Outdoor	4 Options
<b>PHC-6</b> = 6-Station controller with Wi-Fi connection <b>PHC-12</b> = 12-Station controller with Wi-Fi connection <b>PHC-24</b> = 24-Station controller with Wi-Fi connection	<b>00</b> = 120 VAC <b>01</b> = 230 VAC	<b>(blank)</b> = Outdoor model (internal transformer)  <b>i</b> = Indoor model (plug-in transformer)	<b>(blank)</b> = No option <b>E</b> = 230 VAC with European connections <b>A</b> = 230 VAC with Australian connections (outdoor model has internal transformer with cord)

### Examples:

PHC-2400 = 24 station 120 VAC outdoor plastic controller