

PRO-LUBE™

Christy's™

PRODUCT SPECIFICATIONS



PRODUCT TYPE: Water Dispersible Pipe Joint Lubricant

DESCRIPTION: Pro-Lube™ is a water-soluble pipe joint lubricant for joining all types of gasketed pipe and fittings. Pro-Lube™ has a paste like consistency, allowing it to “hang” on the pipe for optimum lubricity. Pro-Lube™ contains no petroleum and will not support bacterial growth. Pro-Lube™ will not deteriorate natural or synthetic rubber, plastic gaskets, stainless steel, ductile or cast iron. Pro-Lube™ is ideal for application on PVC, Clay, Asbestos Cement, Cast Iron, and Concrete pipe. Pro-Lube™ will not impart any objectionable taste or odor into the system, when used in accordance with AWWA specifications.

TECHNICAL:

Form:	Paste Like
Color:	Amber
Phosphates:	None
Free Fatty Acids	1%-3% (as oleic)
Total Alkalinity	100 mg per gram, KOH Equivalent
Toxicity:	None
Boiling Point	> 220° F
Flash Point	> 250° F

Pro-Lube™ is suitable for application temperatures down to 0°F, and is stable from -10°F to 150°F.

Pro-Lube™ is a mixed fatty acid soap dispersed in glycols and water solvents with a clay pigment filler and is water soluble (except clay).

SPECIFICATIONS & INDUSTRY LISTINGS:

Pro-Lube™ is listed by the National Sanitation Foundation for use on potable water and carries the



shield. Pro-Lube™ conforms to all applicable AWWA specifications for pipe joint lubricant.

SPECIAL CONSIDERATIONS: For safety and health precautions please consult our Material Safety Data Sheet on this product.

PACKAGING & HANDLING: Pro-Lube™ is available in resealable Pint, Quart, Gallon and 5 Gallon containers. When stored properly, Pro-Lube has a minimum of 3 years shelf-life.