

# Christy's™

## RED HOT CLEAR GLUE® Low Voc

## PRODUCT SPECIFICATIONS





**PRODUCT TYPE:** PVC Solvent Cement – LOW VOC

**DESCRIPTION:** Red Hot Clear Glue™ is a very aggressive, clear, medium bodied, fast setting PVC solvent cement. It is chemically the “hottest” solvent cement formulation available on the market today. It is designed to be used on all schedules and classes of PVC pipe through 8", schedule 80 through 4". Red Hot is ideal for both quick pressurization and demanding conditions. Red Hot Clear is our best solvent for all OEM PVC applications through 8", including wet or cold condition applications, that require a clean finished joint. Red Hot Clear Glue™ does not require the use of a primer, unless specified by local code.

**APPLICATIONS:** Red Hot Clear Glue™ is for use on all types of PVC plastic pipe applications, Type I and Type II. It is approved for pressure and non-pressure, potable and non-potable, water, turf, ag, conduit, foam core, sewer, DWV and flexible PVC piping. In high pressure, large diameter or very demanding applications, use of purple or clear primer is recommended. In OEM applications, we recommend our Red Hot Clear Glue™ and Red Hot Clear Primer™ if necessary.

Installation instructions are located on each can as well as in our installation brochure. We recommend that you also follow the pipe and fitting manufacturers directions in conjunction with our instructions to insure a viable joint. Red Hot is considered a fast setting solvent cement, work quickly to assure a quality joint.

### **SPECIFICATIONS & INDUSTRY LISTINGS:**

Red Hot Clear Glue™ is a mixture of 100% active solvents and PVC resin. Red Hot Clear Glue™ is listed by the International Association of Plumbing & Mechanical Officials (IAPMO) and carries the  shield. It is additionally listed by NSF International for use on potable water, sewer, drain, waste and vent systems and carries the  symbol and exceeds ASTM D-2564.

COLOR: Clear

VISCOSITY (Brookfield): Minimum 500 cps @ 73 ± 2° F

SPECIFIC GRAVITY: 0.96 ± 0.040

MAX VOC EMISSIONS: 510 G/L, per SCAQMD Rule 1168, Method 316A, Red Hot

Clear– Low VOC is approved for use in the SCAQMD and related district areas for solvent cements requiring reduced emissions.

**SPECIAL CONSIDERATIONS:** For safety and health precautions please consult our Material Safety Data Sheet on this product. Always use in a well-ventilated environment. ***Never test with compressed gas or air.*** For solvent cementing in very cold conditions, please consult our cold weather guidelines.

### **PACKAGING & HANDLING:**

Red Hot Clear Glue™ is available in Quart and Gallon containers. The “shelf life” of Red Hot Clear Glue™ is 3 years in an unopened can from the date stamped on the can. Always seal the can tightly between uses, to prevent the solvent from becoming thickened, stringy or jelled. If the solvent becomes thickened, stringy or jelled, dispose of properly, it cannot be “re-activated” or thinned.