





## PRODUCT SPECIFICATIONS



**PRODUCT TYPE:** PVC & CPVC Primer

**DESCRIPTION:** Red Hot Clear Primer™ is a clear, thin-bodied, ultra aggressive, very fast acting industrial grade PVC/CPVC primer. It is chemically "hotter" than Purple Primer™. It is ideal for OEM applications that require a clean finished joint. It is designed to be used on all schedules and classes of PVC and CPVC as well as PVC profiles that require priming.

APPLICATIONS: Apply Red Hot Clear Primer™ prior to applying solvent cement to both mating surfaces. Proper primer application is critical, it should be "scrubbed" into both the pipe and fitting surfaces – both cleaning and softening both surfaces. Christy's™ Red Hot Clear Primer™ can be used for all types of PVC plastic pipe applications, Type I and Type II as well as CPVC applications. It is approved for pressure and non-pressure, potable and non-potable, water, turf, ag, conduit, foam core, sewer,and DWV PVC applications. Installation instructions are located on each can as well as in our installation brochure. We recommend that you also follow the pipe and fitting manufacturers directions in conjunction with our instructions to insure a viable joint.

## **SPECIFICATIONS & INDUSTRY LISTINGS:**

Red Hot Clear Primer™ is a mixture of 100% active solvents, there are no resins or fillers in the product. Red Hot Clear Primer™ is listed by NSF International for use on potable water, sewer, drain, waste and vent systems and carries the (NSF) symbol and exceeds ASTM F-656

COLOR: Clear
VISCOSITY (Brookfield): Water Thin
SPECIFIC GRAVITY: 0.87 ± 0.040

MAX VOC EMISSIONS: 650 G/L, per SCAQMD Rule 1168, Method 316A, Red Hot Clear Primer™ is approved for use in the SCAQMD and related district areas for solvent weld applications requiring primer.

SPECIAL CONSIDERATIONS: For safety and health precautions plea

SPECIAL CONSIDERATIONS: For safety and health precautions please consult our Material Safety Data Sheet on this product. Always use in a well-ventilated environment. *Never test with compressed gas or air.* For solvent cementing in very cold conditions, please consult our cold weather guidelines. Always wear safety gloves and avoid spills.

## **PACKAGING & HANDLING:**

Red Hot Clear Primer<sup>™</sup> is available in Quart and Gallon containers. The "shelf life" of Red Hot Clear Primer<sup>™</sup> is 3 years in an unopened can from the date stamped on the can. Always seal the can tightly between uses, to prevent the solvent from "flashing off" or evaporating.