

SERIES 38

SPECIFICATIONS

The Hose Connection Vacuum Breaker shall prevent cross connection of contaminated water into the potable water supply caused by back-siphonage.

It shall consist of a single check with an atmospheric breaker vent.

The device shall have a break-away set-screw for tamper proof protection and permanent installation. All parts shall be made of corrosion resistant materials and b e **100% made in USA.**

The backflow preventer shall be suitable for **supply pressure up to 125 psig and water temperature from 33°F to 180°F.**

The unit shall meet the requirements of the following standards: **ASSE 1011, CSA B64.2 and IAPMO.**

The device shall be manufactured by **CONBRACO INDUSTRIES, INC., Matthews, North Carolina**.

FEATURES

38-304

- Tamper proof protection
- Corrosion resistant
- Manual drain feature on stem

38P

- High density thermoplastic body
- Tamper proof protection
- Lightweight and durable
- Corrosion resistant
- Manual drain feature on stem

38-404

- For wall and yard hydrant application
- Tamper proof protection
- Corrosion resistant
- External manual drain feature for freezing conditions

DIMENSIONS (in.)WEIGHTS (lbs.)

MODELS	Α	В	WT./100
38-304	1-5/16	1-1/4	16.8
38P	1-3/4	1-7/16	7.0
38-404-01/03	1-15/16	1-9/16	37.0
38-404-AS	1-15/16	1-5/16	30.0

3/4" Hose Connection Vacuum Breaker







38-304-01/03				
NO.				
38-404-01				
38-404-03				
38-404-AS				

38-404-AS
FINISH
SATIN BRASS
SATIN CHROME
SATIN BRASS

APPROVALS

The Series 38 is approved under: **ASSE 1011 CSA B64.2** and **IAPMO.**







SPEC 38 Series

www.conbraco.com