


FIG. 110 ADJUSTABLE CLEVIS HANGER, LIGHTWEIGHT, DOMESTIC
FIG 110GI ADJUSTABLE CLEVIS HANGER, ELECTRO-GALVANIZED LIGHTWEIGHT



"E" dimension includes exposed rod threads beyond bottom of the hex nut. Exposed rod thread dimension is equal to the diameter of the rod used.

- Material:** Carbon steel.
- Finish:** Plain, electro-galvanized or painted.
- Service:** Designed for the suspension of light stationary pipe or conduit.
- Approvals:** Complies with Federal Specification WW-H-171-E (Type# 12) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 1). Galvanized and coated only.
- Ordering:** Specify pipe size, figure number and finish.
- Notes:** Conduit comes in various outside diameters. Verify outside diameter of conduit is equal to outside diameter of schedule 40 steel pipe.



PIPE SIZE	PIPE OD	MATERIAL SIZE		BOLT	A	B	C	E	F	WGT EACH (lbs)	MAX REC LOAD (lbs)
		TOP	BOTTOM								
1/2	0.840	18ga x 7/8	18ga x 7/8	1/4	3/8	1 3/4	2 1/8	1	1/2	0.12	150
3/4	1.050	18ga x 7/8	18ga x 7/8	1/4	3/8	1 13/16	2 5/16	1 1/16	1/2	0.12	250
1	1.315	18ga x 7/8	18ga x 7/8	1/4	3/8	2 1/8	2 3/4	1 5/16	3/4	0.12	250
1 1/4	1.660	18ga x 7/8	18ga x 7/8	1/4	3/8	2 1/2	3 1/4	1 3/4	15/16	0.18	250
1 1/2	1.900	14ga x 7/8	16ga x 7/8	1/4	3/8	2 3/16	3 13/16	2 1/16	1 1/8	0.24	250
2	2.375	14ga x 7/8	16ga x 7/8	1/4	3/8	3 5/16	4 1/2	2 9/16	1 1/4	0.26	250
2 1/2	2.875	12ga x 1 3/16	14ga x 1 3/16	1/4	1/2	4 1/2	5 5/16	3 7/16	2 1/16	0.58	350
3	3.500	12ga x 1 3/16	14ga x 1 3/16	1/4	1/2	4 13/16	6 9/16	3 3/4	1 7/8	0.66	350
3 1/2	4.000	11ga x 1 3/16	14ga x 1 3/16	5/16	1/2	5 15/16	7 7/8	4 7/8	2 5/8	0.82	350
4	4.500	11ga x 1 3/16	14ga x 1 3/16	3/8	1/2	6 1/16	8 5/16	5	2 3/8	0.94	400