

SUBMITTAL INFORMATION

Stainless Steel Inserts - (Insert-xx style)



STAINLESS STEEL INSERTS FOR POLYETHYLENE PIPE (PEP) OR TUBING (PET)



70 Series For Polyethylene Pipe (PEP)

		-	-		-
CATALOG	NOMINAL	PEP	APPROX.	STD.	✓ SUBMITTED
Number	SIZE	ID	WT. LBS.*	PKG. QTY.	ITEM(S)
INSERT-71	3/4"	0.824	4.4	100	
** INSERT-53-72	1"	1.049	2.9	50	
♦** INSERT-53-72-Q	1"	1.049	2.9	50	
INSERT-73	1-1/4"	1.380	5.8	75	
INSERT-74	1-1/2"	1.610	5.5	45	
INSERT-75	2"	2.067	9.7	50	

50 series For Polyethylene Tubing (PET)

CATALOG Number	Nominal Size	PET ID	APPROX. Wt. Lbs.*	STD. PKG. QTY.	✓ SUBMITTED ITEM(S)
INSERT-51	3/4"	0.681	4.8	200	
INSERT-52	1"	0.875	4.2	100	
** INSERT-53-72	1-1/4"	1.069	2.9	50	
♦** INSERT-53-72-Q	1-1/4"	1.069	2.9	50	
INSERT-54	1-1/2"	1.263	3.1	25	
INSERT-55	2"	1.653	6.0	40	
♦ INSERT-54-Q	1-1/2"	1.263	2.6	30	
♦ INSERT-55-Q	2"	1.653	5.8	50	

^{*} Weights for insert stiffeners are for standard package quantities.

FEATURES

- Insert stiffeners conform to the AWWA Standard C901 for Polyethylene (PE) Pressure Pipe and Tubing.
- Insert stiffeners are solid 304 tubular stainless steel (ASTM 240-92B).
- Dimpled and flanged to retain placement within the service line.
- Key lock construction with a minimum of two key locks to maintain solid structural integrity.

Note: Consult pipe or tubing manufacturer for specific installation requirements. Ford recommends using insert stiffeners when using plastic pipe or tubing.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

http://www.fordmeterbox.com

Submitted By:

06/01/06	

^{**}Insert -53 and -72 fit both 1-1/4" plastic tubing (1.069 I.D.) and 1" plastic pipe (1.049 I.D.).

[♦] These inserts are specifically designed and required for Quick Joint fittings. They are not interchangeable with other Compression Fittings.