

# Powered by the Impossible

## The next generation of circulators

The Grundfos ALPHA will change the way you view circulators. With its permanent magnet motor design, this energy efficient circulator reduces power consumption by 50% or more. The unique patented AUTOADAPT™ feature controls pump performance automatically within defined performance range, ensuring lowest possible energy consumption without sacrificing comfort.

For installation, you now have the flexibility to use either our unique ALPHA Plug with line cord or the new ALPHA with terminal box for conduit connection applications. The choice is yours.











Cast Iron ALPHA 15-55F/LC

# THE UNIQUE FEATURES OF THE GRUNDFOS ALPHA™



Unique ALPHA Plug with line cord



Terminal box for conduit connection applications



Large display shows current energy consumption in Watts



Large display shows estimated flow in gallons per minute



A one button, easyto-use interface



Nut capture



Compact design



Stainless steel and cast iron pump housing available



Integrated check-valve (optional)



#### **Technical Data:**

Flow Range: 0 to 21 GPM

**Head Range:** 0 to 19 Feet

1X115V Motor:

Min. Fluid Temperature: 36°F (2°C)


Max. Fluid Temperature: 230°F (110°C)

Max. Working Pressure: 150 PSI

Watts: 5-45W

0.65A Amps:

#### **Performance Curve:**




3 Constant Pressure Settings


**Black:** 3 Fixed Speed Settings

## **Product Offering:**


Model	Description	Part Number		
ALPHA 15-55F	Cast iron flange with terminal box	59896877		
ALPHA 15-55FR	Cast iron rotated flange with terminal box	59896878		
ALPHA 15-55SF	Stainless flange with terminal box	59896879		
ALPHA 15-55F/LC	Cast iron flange with line cord	59896832		
ALPHA 15-55FR/LC	Cast iron rotated flange with line cord	59896833		
ALPHA 15-55SF/LC	A 15-55SF/LC Stainless flange with line cord			
	Service Kit - Line cord	91130247		
	Service Kit - Terminal box	91130312		

## **Dimensional Drawing:**





Α	В	С	D	Е	F	G	Н	I	J	K
6-1/2	6-3/16	4-15/16	3-13/16	2-3/8	3-7/16	4-1/8	5-3/8	6-11/16	5-1/4	6-1/2



L-AL-SL-001 4/10 (US)

U.S.A. GRUNDFOS Pumps Corporation 17100 West 118th Terrace Olathe, Kansas 66061 Phone: (913) 227-3400 Telefax: (913) 227-3500 Canada GRUNDFOS Canada Inc. 2941 Brighton Road Oakville, Ontario L6H 6C9 Phone: (905) 829-9533 Telefax: (905) 829-9512







