


Position	Count	Description	Unit price
	1	<p><b>UPS 26-99 FC</b></p>  <p>Product photo could vary from the actual product</p> <p>Product No.: 52722512</p> <p>The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump is characterized by:</p> <ul style="list-style-type: none"> <li>* Ceramic shaft and radial bearings.</li> <li>* Carbon axial bearing.</li> <li>* Stainless steel rotor can and bearing plate.</li> <li>* Corrosion-resistant impeller, Composite, PES.</li> <li>* Cast iron pump housing.</li> </ul> <p>The motor is a 1-phase motor. No additional motor protection is required.</p> <p><b>Liquid:</b></p> <p>Liquid temperature range: 35.6 .. 230 °F Liquid temp: 158 °F Density: 61.01 lb/ft³</p> <p><b>Technical:</b></p> <p>Approvals on nameplate: UL, CSA</p> <p><b>Materials:</b></p> <p>Pump housing: Cast iron EN-JL1030 ASTM 30 B</p> <p>Impeller: Composite, PES</p> <p><b>Installation:</b></p> <p>Maximum ambient temperature: 104 °F Ambient max at 176°F liquid: 176 °F Maximum operating pressure: 145 psi Flange standard: USA Oval Type of connection: C.I. Flange Pipe connection: 2 - Bolt Flange Pressure stage: 10 Port-to-port length: 6 1/2 in</p> <p><b>Electrical data:</b></p>	On request



Company name: Mountain States Supply

Created by: -

Phone: -

Fax: -

Date: -

Position	Count	Description	Unit price
		Number of poles: 2	
		Power input in speed 1: 150 W	
		Power input in speed 2: 179 W	
		Max. power input: 197 W	
		Rated power - P2: 0.161 HP	
		Main frequency: 60 Hz	
		Rated voltage: 1 x 115 V	
		Current in speed 1: 1.3 A	
		Current in speed 2: 1.5 A	
		Current in speed 3: 1.8 A	
		Capacitor size - run: 20 µF/180 V	
		Insulation class (IEC 85): F	
		<b>Others:</b>	
		Gross weight: 10.3 lb	

Description	Value
Product name:	UPS 26-99 FC
Product No.:	52722512
EAN:	5700834818707
Technical:	
Speed Number:	3
Max flow:	33 US gpm
Head max:	28.9 ft
Approvals on nameplate:	UL, CSA
Valve:	pump with built-in isolating and non-return valves
Materials:	
Pump housing:	Cast iron
	EN-JL1030
	ASTM 30 B
Impeller:	Composite, PES
Installation:	
Maximum ambient temperature:	104 °F
Ambient max at 176°F liquid:	176 °F
Maximum operating pressure:	145 psi
Flange standard:	USA Oval
Type of connection:	C.I. Flange
Pipe connection:	2 - Bolt Flange
Pressure stage:	10
Port-to-port length:	6 1/2 in
Liquid:	
Liquid temperature range:	35.6 .. 230 °F
Liquid temp:	158 °F
Density:	61.01 lb/ft³
Electrical data:	
Number of poles:	2
Power input in speed 1:	150 W
Power input in speed 2:	179 W
Max. power input:	197 W
Rated power - P2:	0.161 HP
Main frequency:	60 Hz
Rated voltage:	1 x 115 V
Current in speed 1:	1.3 A
Current in speed 2:	1.5 A
Current in speed 3:	1.8 A
Capacitor size - run:	20 µF/180 V
Insulation class (IEC 85):	F
Motor protection:	CONTACT
Thermal protec:	internal
Controls:	
Pos term box:	9H
Others:	
Gross weight:	10.3 lb

