



# Gauges & Thermometers

*All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions.*

## Dry Gauges

### styles

- standard
- Flutterguard™
- Contractor Pressure
- Compound
- Vacuum
- Welding

### materials

- ABS
- Brass
- Stainless steel

### mount type

- lower
- center back

### face size

- 1½"
- 2"
- 2½"
- 3½"
- 4½"

(contractor pressure gauge only)



**Welding  
gauge**



**Vacuum  
gauge**



**Brass Standard  
gauge**



**Flutterguard™  
gauge**



**Standard  
center back mount  
gauge**



**Contractor Pressure  
gauge**



**Stainless Steel Standard  
gauge**



**Compound  
gauge**

## Liquid Filled Gauges

### styles

- standard

### materials

- ABS
- Brass
- Stainless steel

### face size

- 2½"
- 4"

### mount type

- lower
- center back



**Brass gauge**



**Stainless Steel  
center back mount  
gauge**



**ABS gauge**

## Thermometers & Miscellaneous

### thermometers

- bi-metal
  - model 30
  - model 31
  - model 50
  - model 52
  - pocket
- magnetic surface mount
- threaded thermowells
- 180° steam gauge siphon



**Bi-metal thermometer**



**Magnetic thermometer**



**Pocket Bi-metal thermometer**



**180° steam gauge siphon**



**threaded thermowells**

## Hose Coupling Safety

- Use Dixon couplings, retention devices and accessory products ***only*** for their intended service.
- All recommendations of the Hose Manufacturer, and the Coupling Manufacturer, must be employed with regards to **Size, Temperature, Application, Media, and Pressure** when selecting the components for a hose assembly.
- All finished hose assemblies should be tested in accordance with the **Rubber Manufacturers Association** recommendations.
- All hose assemblies should be thoroughly inspected prior to each use to insure they are undamaged, and properly coupled.
- Use safety clips on couplings, and King Safety Cables on assemblies where required by the manufacturer, as well as State and Federal regulations.
- Call Dixon (1-800-355-1991) for advice on couplings, retention devices, and accessories for your application.



**Dixon Valve & Coupling Co.**  
800 High Street  
Chestertown, MD 21620  
800.355.1991  
Fax: 800.283.4966  
[www.dixonvalve.com](http://www.dixonvalve.com)