

HYBRID

Rain Dial® Plus SERIES

CONTROLLERS



HYBRID

Rain Dial® Plus series

CONTROLLERS



Taking the popular Rain Dial family of controllers to the next plateau, Irritrol Systems' Rain Dial Plus offers a host of enhanced performance features. Electrical surge protection resists damage from both lightning and power surges. Non-volatile memory holds programs during power failures. Odd/even day watering options offer exceptional scheduling flexibility. Water budgeting increases or decreases valve run times from 0 percent to 200 percent. A unique modular design permits fast and easy servicing. And, a snap-out control panel facilitates remote programming.

For added convenience, Rain Dial Plus also offers KwikStart™, a remote control system designed to work exclusively with this series.

Rain Dial Plus — the controller of choice for residential applications.

Irritrol®
SYSTEMS

Rain Dial® Plus SERIES

CONTROLLERS

6, 9 and 12

station models (outdoor/indoor)

Features

- Three independent programs offer concurrent operation capability
- 365-day calendar with automatic weekday calculation for odd/even day watering options and auto leap year adjustment
- Easy-to-read programming dial and large, self-prompting LCD
- Short-station detection and display
- Multiple language capabilities (English, French, German, Italian and Spanish)
- Easy-to-understand icons
- Automatic, semi-automatic and timed-manual operation
- Modular design allows easy removal of control module without disturbing valve wiring
- "Anywhere programming" feature provides convenient remote programming while under battery power
- Self-diagnostic electronic circuit breaker identifies and overrides an electrical malfunction of a valve
- Non-volatile memory holds program during power failure
- Battery backup keeps current time and date during power failure (battery included)
- Electrical surge protection (on both input and output lines) resists damage from lightning storms and power surges
- Start-time stacking when more than three valves are on
- Water budgeting option for each program (0-200%)
- Program erase for each program
- Master valve/pump start circuit
- Weather-resistant plastic, locking cabinet with an internal transformer (outdoor models)
- Durable, plastic cabinet with an external transformer (indoor models)
- Wall mount
- UL, CUL and CE listed

Operating Specifications

- Station run times: 1-59 minutes in 1-minute increments or 1-5.9 hours in .1-hour (6 min.) increments
- Start times: 3 per program for up to 9 daily starts
- Watering schedule: 365-day calendar with automatic weekday calculation for odd/even day watering options

Electrical Specifications

- Transformer input: 120 VAC, 60Hz
- Transformer output: 24 VAC, 1.25 amps
- Maximum output per station: 24 VAC, .5 amp
- Maximum total output: 24 VAC, 1.0 amp (including pump relay/master valve)
- Battery backup: 9-volt alkaline battery (included)

Dimensions

Outdoor	Indoor
Height: 7 ¾"	Height: 7 ¾"
Width: 10 ¾"	Width: 7"
Depth: 4"	Depth: 3 ¾"

*KwikStart™ Remote Control Option for the new Rain Dial Plus**

- Attaches to Rain Dial Plus controllers to provide convenient remote-controlled operation
- Rain Dial Plus automatic and manual operations remain functional during use of remote control
- Transmitter is preset to operate up to 12 controller stations, but is adjustable from one to 64 stations
- Transmitter power source: 9-volt alkaline battery (supplied)
- Receiver power source: 5 VDC @ 10 mA (supplied from controller)
- Preset station run time: 10 minutes
- Transmitter operating range/line of sight: approximately 160'-300'
- Operating temperature: +14°F to +140°F
- Storage temperature: -22°F to +149°F

Optional Accessories

- KwikStart™ remote control system kit (KSR-KIT) includes:
 - KS-Remote transmitter (KSR-T)
 - KS-Remote receiver (KSR-R)
 - KS-Remote 4' cable harness (KSR-03)
- KwikStart™ remote adapter kit (KSR-ADP)**

* The KwikStart™ remote system is compatible with Rain Dial Plus controllers with manufacturing date codes on or after Oct. 4, 2000 (100400).

** KSR-ADP sold separately.



HYBRID—Residential

Rain Dial® Plus SERIES

CONTROLLERS

MODELS HOW TO SPECIFY

Model	RD-6PLUS-EXT	
	Number of Stations	Outdoor/Indoor Mount Option
RD6PLUS-EXT	6	outdoor
RD9PLUS-EXT	9	outdoor
RD12PLUS-EXT	12	outdoor
RD6PLUS-INT	6	indoor
RD9PLUS-INT	9	indoor
RD12PLUS-INT	12	indoor

Irritrol®
SYSTEMS

BEYOND THE EXPECTED

5825 Jasmine Street, Riverside, CA 92504-1183
909/785-3623 Fax 909/785-3795
<http://www.irritrolsystems.com>