S4510-CAN

NONE

2-16-70

CHECKED BY:

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

4510, 4530 SERIES-CAN

FIGURE NUMBER

DRAWING NUMBER

PLUMBING & DRAINAGE PRODUCTS

959 Alness Street, North York, Ontario M3J 2J1


TEL: (416) 736-9610 FAX: (416) 736-3789


LOCATION

CLEANOUT TEES

WITH COUNTERSUNK PLUG AND ROUND ACCESS COVER

FUNCTION: Used in concealed drainage lines where a cleanout is desired. Removable face-of-wall cover allows easy access to closure plug.





LESS COVER AND SCREW

WITH COVER AND SCREW

F	ig. 4510S GASKET SEAL - IRON PLUG	Fig. 4530S
□□F	ig. 4511S GASKET SEAL - BRONZE PLUG	Fig. 4531S
	ig. 4512S TAPER THREAD - BRONZE PLUG	Fig. 4532S

Α	В	С	D	Е	F
SIZE	DIA		SIZE		
02 (50)	4 1/4 (110)	10 1/2 (265)	1 1/2 (38)	6 1/4 (160)	2 (51)
03 (80)	5 1/2 (140)	11 3/4 (300)	2 1/2 (64)	7 (180)	2 1/2 (64)
04 (100)	5 1/2 (140)	12 (305)	3 1/2 (89)	7 (180)	3 (76)
05 (125)	7 (180)	*13 (330)	4 1/2 (115)	8 1/2 (215)	4 (100)
06 (150)	9 1/4 (235)	16 (405)	6 (150)	9 (230)	4 1/2 (115)

^{*} This Dimension becomes 15 (380) for the 4512 and 4532.

Spigot Outlet Sized for Service Weight and/or NO-HUB

REGULARLY FURNISHED:

Duco Cast Iron Cleanout Tee and Countersunk Plug with Stainless Steel Round Cover and Screw as Indicated by Figure Number Selected.

VARIATIONS:

Longer Center Screw (Specify Length)

OPTIONAL MATERIALS: Polished Bronze Cover -PB Prime Coated Steel Cover -PC

"T" Handle Plug -TP

(Plug Tapped 1/4" (6) -20 Thread)

Vandal Proof Screw -U (Fig. 4530 Series)

NOTE: Dimensions shown in

NO-HUB Both Ends 2 (50), 3 (80), & 4" (100) parentheses are in millimeters.

sizes only

F E		Revised Variations Added Metric	JJ EMB	CL BS	 VOLUME CUBIC FEET
REV.	DATE	DESCRIPTION	BY	CKD. BY	

FIGURE NUMBER **4510 SERIES 4530 SERIES-CAN**