

2110, 2115	DRAWN BY: PJ	CHECKED BY: TD	APPROVED BY: TD	DATE: 5-17-85	SCALE: NONE	SIZE A	DRAWING NUMBER S2110	G																		
	SMITH® JAY R. SMITH MFG. CO.® DIVISION OF SMITH INDUSTRIES, INC. POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF: MEMBER OF:								LOCATION 																	
	FLOOR DRAINS WITH 8 1/2" (215) ROUND TOPS																									
	MEDIUM DUTY DRAINS																									
	FUNCTION: Used in moderate traffic areas where waste water contains no sediment or debris and floor construction requires shallow drain body. Body flange and flashing collar serve as anchor in on-grade locations and as flashing clamp when installed in waterproof floors. Free Area 14.25 SQ IN (360) SQ CM Seepage Openings Collar Can Be Used As Flashing Clamp (When Specified) Trap Primer Connection (When Specified) ** Fig. 2110C ... CAULK OUTLET Fig. 2110Y ... NO-HUB OUTLET <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th>A SIZE</th> <td>02 (50)</td> <td>03 (80)</td> <td>04 (100)</td> <td>06 (150)</td> </tr> <tr> <th>B</th> <td colspan="2">3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded</td> <td colspan="2">3 3/4 (95) NO-HUB Only</td> </tr> </table> Fig. 2115C ... CAULK OUTLET Fig. 2115T ... THREADED OUTLET <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th>A SIZE</th> <td>02 (50)</td> <td>03 (80)</td> <td>04 (100)</td> </tr> <tr> <th>B</th> <td>4 1/4 (110)</td> <td>3 3/4 (95)</td> <td>3 1/4 (83)</td> </tr> </table> REGULARLY FURNISHED: Duco Cast Iron Body and Flashing Collar with Cast Iron Bar Grate. VARIATIONS: ☐ Closure Plug -XP (Fig. 2110 only) ☐ Deflector Grate -DG ☐ Dome Grate -D ☐ Flat Bottom Strainer -FBS (Fig. 2110 only) ☐ L Speedi-Set Service Weight (Fig. 2110 only) ☐ LXH Speedi-Set Extra Heavy (Fig. 2110 only) ☐ NO-HUB Adaptor (Specify Fig. 2646Y) (Fig. 2115 only) ☐ Sediment Bucket -B ☐ Square Top -S ☐ Trap Primer Connection -P050 1/2" (13) & -P075 3/4" (19) ☐ Vandal Proof Grate -U ☐ Wide Flange Deck Drain (Specify Fig. DX2565) ☐ T Threaded Outlet OPTIONAL MATERIALS: ☐ Ductile Iron Grate -M ☐ Galvanized Cast Iron -G ☐ Nickel Bronze Top -NB ☐ Polished Bronze Top -PB ☐ Stainless Steel (Specify Fig. 9710)									A SIZE	02 (50)	03 (80)	04 (100)	06 (150)	B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only		A SIZE	02 (50)	03 (80)	04 (100)	B	4 1/4 (110)	3 3/4 (95)
A SIZE	02 (50)	03 (80)	04 (100)	06 (150)																						
B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only																							
A SIZE	02 (50)	03 (80)	04 (100)																							
B	4 1/4 (110)	3 3/4 (95)	3 1/4 (83)																							