

H	SMITH® CUSTOMER DRIVEN	JAY R. SMITH MFG. CO.® DIVISION OF SMITH INDUSTRIES, INC. POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com	ASPE	PDI INSTITUTE	ASSE	LOCATION																																								
FLOOR DRAINS WITH 8 1/2" ROUND ADJUSTABLE TOPS MEDIUM DUTY DRAINS WITH TRACTOR GRATE AND ADJUSTABLE TOP FUNCTION: Used in moderate traffic areas where waste water contains no sediment or debris and floor construction requires shallow drain body. Body flange and flashing collar serve as anchor in on grade locations and as flashing clamp when installed in waterproof floors. Adjustable top collar permits accurate positioning of grate to meet finished floor level. Free Area 13 SQ IN (84) SQ CM ☐ Fig. 2320C ... CAULK OUTLET ☐ Fig. 2320Y ... NO-HUB OUTLET <table><thead><tr><th>A SIZE</th><th>02 (50)</th><th>03 (80)</th><th>04 (100)</th><th>06 (150)</th></tr></thead><tbody><tr><td>B</td><td>3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded</td><td></td><td>3 3/4 (95) NO-HUB Only</td><td></td></tr></tbody></table> ☐ Fig. 2325C ... CAULK OUTLET ☐ Fig. 2325T ... THREADED OUTLET <table><thead><tr><th>A SIZE</th><th>02 (50)</th><th>03 (75)</th><th>04 (100)</th></tr></thead><tbody><tr><td>B</td><td>4 1/4 (110)</td><td>3 3/4 (95)</td><td>3 1/4 (83)</td></tr></tbody></table> *This Dimension to Internal Stop of Speedi-Set Gasket. Øadd 3/16"(5) when bronze top is specified REGULARLY FURNISHED: Duct Cast Iron Body and Flashing Collar with Adjustable Top and Tractor Grate. VARIATIONS: ☐ Closure Plug -XP (Fig. 2320 only) ☐ Extension (Specify Height) -E ☐ Flat Bottom Strainer -FBS (Fig. 2320 only) ☐ L Speedi-Set Service Weight (Fig. 2320 only) ☐ LXH Speedi-Set Extra Heavy (Fig. 2320 only) ☐ NO-HUB Adaptor (Specify Fig. 2646Y) (Fig. 2325 only) ☐ Square Top -S * ☐ Trap Primer Connection -P050 1/2"(13) & -P075 3/4"(19) ☐ Vandal Proof Grate -U ☐ T Threaded Outlet ☐ Bucket -B OPTIONAL MATERIALS: ☐ Ductile Iron Grate -M ☐ Galvanized Cast Iron -G ☐ Nickel Bronze Top -NB ☐ Polished Bronze Top -PB *Not available on Fig. 2320T threaded outlet drain. NOTE: Dimensions shown in parentheses are in millimeters. <table><tr><td rowspan="2">FIGURE NUMBER</td><td>H</td><td>12-1-08</td><td rowspan="2">Revised Variations Revised 2320 A-Size Table Changed Millimeters</td><td>RN</td><td>CL</td><td rowspan="2">WEIGHT POUNDS</td><td rowspan="2">VOLUME CUBIC FEET</td><td rowspan="2">FIGURE NUMBER 2320,2325</td></tr><tr><td>G</td><td>11/17/05</td><td>JJ</td><td>CL</td></tr><tr><td></td><td>REV.</td><td>DATE</td><td>DESCRIPTION</td><td>BY</td><td>CKD. BY</td><td></td><td></td><td></td></tr></table>							A SIZE	02 (50)	03 (80)	04 (100)	06 (150)	B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only		A SIZE	02 (50)	03 (75)	04 (100)	B	4 1/4 (110)	3 3/4 (95)	3 1/4 (83)	FIGURE NUMBER	H	12-1-08	Revised Variations Revised 2320 A-Size Table Changed Millimeters	RN	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 2320,2325	G	11/17/05	JJ	CL		REV.	DATE	DESCRIPTION	BY	CKD. BY			
A SIZE	02 (50)	03 (80)	04 (100)	06 (150)																																										
B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only																																											
A SIZE	02 (50)	03 (75)	04 (100)																																											
B	4 1/4 (110)	3 3/4 (95)	3 1/4 (83)																																											
FIGURE NUMBER	H	12-1-08	Revised Variations Revised 2320 A-Size Table Changed Millimeters	RN	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 2320,2325																																						
	G	11/17/05		JJ	CL																																									
	REV.	DATE	DESCRIPTION	BY	CKD. BY																																									