

F	SMITH® JAY R. SMITH MFG. CO. DIVISION OF SMITH INDUSTRIES, INC. POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF: LOCATION																																																										
ROOF ACCESSORY																																																											
DOWNSPOUT NOZZLE																																																											
FUNCTION: Used as a parapet overflow or at the base of a wall where a concealed leader discharges rainwater to ground. Nozzle design diverts water away from building, eliminating wall stains. Wall flange covers rough opening and serves as anchor.																																																											
Fig. 1770T																																																											
<table border="1" style="width:100%; border-collapse: collapse; font-size: 10px;"> <tr> <th>A=PIPE</th> <td>02(50)</td> <td>03(75)</td> <td>04(100)</td> <td>05(125)</td> <td>06(150)</td> <td>08(200)</td> <td>10(255)</td> <td>12(305)</td> </tr> <tr> <th>B=DIA</th> <td>2 3/4 (70)</td> <td>4 (100)</td> <td>5 (125)</td> <td>6 (150)</td> <td>7 1/4 (185)</td> <td>9 1/4 (235)</td> <td>11 1/8 (283)</td> <td>13 1/4 (335)</td> </tr> <tr> <th>C=RAD</th> <td>2 3/4 (70)</td> <td>3 1/2 (89)</td> <td>3 7/8 (98)</td> <td>4 3/8 (111)</td> <td>5 (125)</td> <td>5 7/8 (149)</td> <td>7 1/4 (185)</td> <td>8 (205)</td> </tr> <tr> <th>D</th> <td>1 3/8 (35)</td> <td>1 3/8 (35)</td> <td>1 3/8 (35)</td> <td>1 3/8 (35)</td> <td>1 3/8 (35)</td> <td>1 5/8 (41)</td> <td>1 3/4 (44)</td> <td>2 (51)</td> </tr> <tr> <th>E</th> <td>2 1/16 (52)</td> <td>2 1/16 (52)</td> <td>2 1/16 (52)</td> <td>2 1/16 (52)</td> <td>2 1/16 (52)</td> <td>2 3/8 (60)</td> <td>2 3/4 (70)</td> <td>2 15/16 (75)</td> </tr> <tr> <th>F</th> <td>5 5/8 (143)</td> <td>5 5/8 (143)</td> <td>5 5/8 (143)</td> <td>5 5/8 (143)</td> <td>5 5/8 (143)</td> <td>5 15/16 (149)</td> <td>5 3/8 (138)</td> <td>7 9/16 (192)</td> </tr> </table>						A=PIPE	02(50)	03(75)	04(100)	05(125)	06(150)	08(200)	10(255)	12(305)	B=DIA	2 3/4 (70)	4 (100)	5 (125)	6 (150)	7 1/4 (185)	9 1/4 (235)	11 1/8 (283)	13 1/4 (335)	C=RAD	2 3/4 (70)	3 1/2 (89)	3 7/8 (98)	4 3/8 (111)	5 (125)	5 7/8 (149)	7 1/4 (185)	8 (205)	D	1 3/8 (35)	1 3/8 (35)	1 3/8 (35)	1 3/8 (35)	1 3/8 (35)	1 5/8 (41)	1 3/4 (44)	2 (51)	E	2 1/16 (52)	2 1/16 (52)	2 1/16 (52)	2 1/16 (52)	2 1/16 (52)	2 3/8 (60)	2 3/4 (70)	2 15/16 (75)	F	5 5/8 (143)	5 5/8 (143)	5 5/8 (143)	5 5/8 (143)	5 5/8 (143)	5 15/16 (149)	5 3/8 (138)	7 9/16 (192)
A=PIPE	02(50)	03(75)	04(100)	05(125)	06(150)	08(200)	10(255)	12(305)																																																			
B=DIA	2 3/4 (70)	4 (100)	5 (125)	6 (150)	7 1/4 (185)	9 1/4 (235)	11 1/8 (283)	13 1/4 (335)																																																			
C=RAD	2 3/4 (70)	3 1/2 (89)	3 7/8 (98)	4 3/8 (111)	5 (125)	5 7/8 (149)	7 1/4 (185)	8 (205)																																																			
D	1 3/8 (35)	1 3/8 (35)	1 3/8 (35)	1 3/8 (35)	1 3/8 (35)	1 5/8 (41)	1 3/4 (44)	2 (51)																																																			
E	2 1/16 (52)	2 1/16 (52)	2 1/16 (52)	2 1/16 (52)	2 1/16 (52)	2 3/8 (60)	2 3/4 (70)	2 15/16 (75)																																																			
F	5 5/8 (143)	5 5/8 (143)	5 5/8 (143)	5 5/8 (143)	5 5/8 (143)	5 15/16 (149)	5 3/8 (138)	7 9/16 (192)																																																			
NOTE: Dimensions shown in parentheses are in millimeters.																																																											
REGULARLY FURNISHED: Cast Bronze Nozzle and Flange. VARIATIONS: ☐ Bird Screen -BS OPTIONAL MATERIALS: ☐ Nickel Bronze -NB ☐ Polished Bronze -PB																																																											
1770	FIGURE NUMBER 1770		WEIGHT POUNDS 		VOLUME CUBIC FEET 																																																						
	REV.	DATE	DESCRIPTION	BY	CKD. BY																																																						