## SAFETY ECTREAS DUCTTAPES

## KING SAFETY TAPE SPEC SHEET

CATALOG #	SELLING UNIT	DIMENSIONS US	DIMENSIONS METRIC	MAX TEMP	MAX VOLT	COLOR
86001	each	.75" x .007" x 66'	19mm x .18mm x 20mm	176° F/ 80° C	600V	black
	DESCRIPTION				-	
	A general purpose 7 mil tape, weather resistant				- MAR	
	<ul> <li>Use for all mechanical and electrical applications</li> </ul>				100001	
	Use as a primary insulation 600V max				COLUMN TWO IS NOT	
	Flame retardant				A	
	Economical grade of pressure-sensitive vinyl tape				. Ulling	
	Use as a protective outer jacket over splices					
	• UL 510					
KING SA	ΓΕΤΎ ΔΙΙ-WEΔΤ	HER ELECTRICAL TAPE				
CATALOG #		DIMENSIONS US	DIMENSIONS METRIC	MAX TEMP	MAX VOLT	COLOR
86016	each	.75″ x .007″ x 66′	19mm x .18mm x 20mm	-10° C/ 150° C	600V	black
	<ul> <li>Meets ASTM s</li> <li>HH-1595C</li> <li>UL 510, CSA i</li> <li>Excellent adheed</li> </ul>	esion to aluminum/copper co	nductors, plastic, and rubber insulat	ion		
XING SAI	FETY SILVER DU	DIMENSIONS US	DIMENSIONS METRIC	MAX TEMP	MAX VOLT	COLOR
	each	2" x .007" x 60 yds	51mm x .18mm x 55mm			silver
86070						