

KING SAFETY UNFILLED

WIRE CONNECTORS

FOR DRY APPLICATIONS

KING SAFETY UNFILLED WIRE CONNECTOR SPEC SHEET

ORANGE WING UNFILLED WIRE CONNECTOR FOR DRY LOCATIONS

CATALOG #	SELLING UNIT	SPECIFICATIONS
23110	Card of 10	Max Voltage: 300, 600-1000V in fixtures and signs
23120	Clam of 25	Size: 7/16" x 7/8"
23130	Clam of 50	Temp Rating: 221° F/ 105° C
23140	Box of 100	Wire Combinations: Copper/Copper
23150	EZ-Zippak of 500	Wire Size: Min 3 #22 / Max 2 #14
23160	Carton of 1000 (2 bags of 500)	
23170	Carton of 5000 (10 bags of 500)	



WIRE STRIP LENGTH: #22-18 1/2",
#16-14 3/8"

YELLOW NUT UNFILLED WIRE CONNECTOR FOR DRY LOCATIONS

CATALOG #	SELLING UNIT	SPECIFICATIONS
23425	Bag of 20	Max Voltage: 600-1000V in fixtures and signs
23435	Bag of 100	Size: 1-1/8" x 9/16"
23450	Carton of 1000	Temp Rating: 221° F/ 105° C
		Wire Combinations: Copper/Copper
		Wire Size: Min 3 #20 / Max 3 #12



WIRE STRIP LENGTH: 1/2"

RED WING UNFILLED WIRE CONNECTOR FOR DRY LOCATIONS

CATALOG #	SELLING UNIT	SPECIFICATIONS
23210	Card of 6	Max Voltage: 600-1000V in fixtures and signs
23220	Clam of 25	Size: 11/16" x 1-5/16"
23230	Clam of 50	Temp Rating: 221° F/ 105° C
23240	Box of 100	Wire Combinations: Copper/Copper
23250	EZ-Zippak of 500	Wire Size: Min 6 #22 / Max 4 #12
23260	Carton of 1000 (2 bags of 500)	
23270	Carton of 5000 (10 bags of 500)	
23280	Carton of 10000 (20 bags of 500)	



WIRE STRIP LENGTH: 5/8"

BLUE WING UNFILLED WIRE CONNECTOR FOR DRY LOCATIONS

CATALOG #	SELLING UNIT	SPECIFICATIONS
23310	Card of 3	Max Voltage: 600-1000V in fixtures and signs
23320	Clam of 25	Size: 13/16" x 1-9/16"
23330	Box of 50	Temp Rating: 221° F/ 105° C
23340	EZ-Zippak of 250	Wire Combinations: Copper/Copper
23350	Carton of 1000 (4 bags of 250)	Wire Size: Min 4 #14 / Max 2 #6 w/ 1 #12
23360	Carton of 2000 (8 bags of 250)	



WIRE STRIP LENGTH: 11/16"- 3/4"

Complete listing of wire combinations on pages 23-24.

