

Features

- Brass construction
- Fixture-mount design
- Includes a 9 V lithium battery
- Intended for toilet installations with 1-1/2" spud coupling connection
- Electronic infrared sensor with WAVE technology for accurate activation
- Retrofit models require a control stop and vacuum breaker
- 1.28 gpf (4.8 lpf) flush flow rate for low water consumption [K-10673 and K-10666]
- 1.6 gpf (6 lpf) flush flow rate [K-10674 and K-10677]
- Slow-closing piston technology

Codes/Standards Applicable


Specified model meets or exceeds the following:

- ADA
- ICC/ANSI A117.1
- CSA B651
- OBC
- ASME A112.18.1/CSA B125.1
- CSA B125.3
- CSA B64
- ASSE 1037
- FCC 47, Part 15
- EN 55022
- ICES-003 Class B

K-10673

ALSO K-10674, K-10677, K-10666

ADA CSA B651 OBC



Colors/Finishes

· CP: Polished Chrome

Specified Model:

Model	Description	Colors/Finishes
K-10666	Exposed WAVE flush valve retrofit – 1.28 gpf (4.85 lpf)	□ CP
K-10673	Exposed WAVE flush valve – 1.28 gpf (4.8 lpf)	□ CP
K-10674	Exposed WAVE flush valve – 1.6 gpf (6 lpf)	□ CP
K-10677	Exposed WAVE flush valve retrofit – 1.6 gpf (6 lpf)	□ CP

PRODUCT SPECIFICATION

Electronic flush valve shall be made of brass construction. Valve shall feature electronic infrared sensor with WAVE technology for accurate activation. Valve shall be of a fixture-mount design. Product is intended for toilet installations with a 1-1/2" spud coupling connection, and retrofit models require a control stop and vacuum breaker. Valve shall have a 1.28 gpf (4.8 lpf) flow rate for low water consumption [K-10673 and K-10666] or 1.6 gpf (6 lpf) flow rate [K-10674 and K-10677]. Valve includes a 9 V lithium battery. Valve shall have slow-closing piston technology. Product shall be Kohler Model K-_____-CP.

Installation Notes

Install this product according to the installation guide.

ADA, CSA B651, OBC compliant when installed to the specific requirements of these regulations.

