Swing Riser Fittings
Just Got Better...

With LASCO'S New





- Self threading double helix design.
- Easy to install.
- Used with Funny Pipe® and other thick walled  $\frac{1}{2}$ " I.D. Tubing.
- Used in drip irrigation, home sprinkler systems, and other Residential/Commercial irrigation applications.
- Patent Pending.



Part No.	Description	Carton (qty)	Price (ea)
3300-005	½" Elbow, MIPT x Double Helix®	500 (20 Bags/25)	\$.30
3300-007	<sup>3</sup> / <sub>4</sub> " Elbow, MIPT x Double Helix <sup>®</sup>	500 (20 Bags/25)	\$.30
3400-005	½" Male Adapter, MIPT x Double Helix®	100 (4 Bags/25)	\$.30
3400-007	<sup>3</sup> / <sub>4</sub> " Male Adapter, MIPT x Double Helix <sup>®</sup>	100 (4 Bags/25)	\$.30
3201-004	Coupling, Double Helix®	100 (4 Bags/25)	\$.42
3302-005	½" Elbow, FIPT x Double Helix®	100 (4 Bags/25)	\$.60
3101-004	Tee, Double Helix®	100 (4 Bags/25)	\$.69
3100-005	Tee, Double Helix® x Double Helix® x MIPT	100 (4 Bags/25)	\$.60

## **Bidding Specifications:**

## **Swing Riser Fittings**

The fitting should have an external Double Helix® type of barb capable of retaining a flexible polyethylene pipe with an inside diameter of  $.490 \pm .010$  without the use of clamps. The fittings should have a 400-PSI burst rating. The pipe must be thick wall (.10) and made of polyethylene, which is a flexible plastic.

The fitting should be part number \_\_\_\_\_ and is to be manufactured by LASCO, Fittings, Inc., Brownsville, TN. USA.

