SUBMITTAL SHEET

Joint Restraint System For IPS, DPS & DIN Plastic Pipe



PIPE TO FITTING

LH-Series... 2" - 12" IPS Pipe Sizes
LHD-Series... 4" - 24" DPS Pipe Sizes
DLH-Series... 63 - 400MM DIN Pipe Sizes



PIPE TO PIPE

LB-Series... 2" - 12" IPS Pipe Sizes
LBD-Series... 4" - 24" DPS Pipe Sizes
DLB-Series... 63 - 400MM DIN Pipe Sizes



PIPE TO PIPE
LPP-Series... 2" - 12" IPS Pipe Sizes



PIPE TO FITTING - For Gate Valves

LGK-Series... 2" - 12" IPS Pipe Sizes LGKD-Series... 4" - 12" DPS Pipe Sizes DLGK-Series... 63 - 400MM DIN Pipe Sizes



PIPE TO PIPE - For Gate Valves

LG-Series... 2" - 12" IPS Pipe Sizes
LGD-Series... 4" - 12" DPS Pipe Sizes
DLG-Series... 63 - 400MM DIN Pipe Sizes



PIPE TO PIPE - For MJ Gate Valves

LMJ-Series... 2" - 12" IPS Pipe Sizes LMJD-Series... 4" - 12" DPS Pipe Sizes DLMJ-Series... 63 - 400MM DIN Pipe Sizes

SIZES:
MATERIAL:
PRESSURE RATING:
EPOXY COATING:
HARDWARE:

2 - 12" IPS, 4 - 24" DPS & 63 - 400MM DIN

Class 350 Ductile Iron per ASTM A-536, Grade 65-45-12, AWWA C153 350 PSI

350 PSI

ANSI/AWWA C116/A21.16-09, NSF 61 & CSA Z245.20-98, 10-12 MIL Low Alloy Steel ANSI/AWWA C11/A21.11, Optional 304 or 316 stainless

Per IPS, DPS & DIN Pipe Standards

Specification:

All changes of directions and reductions shall be mechanically restrained. Additional adjacent joints shall also be restrained as per manufactures recommendations. Joint Restraints shall be ductile iron and made in accordance with ASTM A-536, Grade 65-45-12 & AWWA C153. All Restraints shall have blunt cast serrations. Machine threaded restraints shall not be allowed. Optional Epoxy Coating shall be fusion bonded epoxy, 10-12 mil thickness. The epoxy coated restraints shall pass 90-Day immersion tests per CSA Z245.20-98. All Joint Restraints shall be manufactured by Leemco, Inc., U.S.A.



Leemco, Inc. 360 S. Mount Vernon Colton, CA. 92324

Ph: (909) 422-0088 Fx: (909) 422-0086

Web: www.leemco.com

Leemco has a large variety of Fittings & Joint Restraints...

Please refer to our IPS, DPS and DIN Price Lists for available Models and Sizes.