


Tag:
Series : FCI500

METAL*AIRE®
Submittal No: FCI500-ECM-EH

Fan Power Air Terminal

Model: FCI500-ECM-EH Series Fan Power Air Terminal With E.C.M. and Electric Heater
Located on the Discharge Port



Casing Size	Inlet Diameter D		Horse Power	Unit Height H	Unit Width W	Unit Length L	Inlet Loc. A	Ind. Inlet Height B	Ind. Inlet Width C	Discharge Loc. E	Discharge Height F	Discharge Width G
	Standard	Optional										
2	8 (203)	6, 10, 12	1/2	17 1/2 (445)	30 (762)	36 (914)	7 (178)	14 (356)	14 (356)	5 (127)	15 (381)	16 (406)
4	12 (305)	8, 10, 14	1/2	17 1/2 (445)	36 (914)	40 (1016)	8 (203)	14 (356)	18 (457)	3 1/4 (83)	17 1/2 (445)	20 (508)
6	16 (406)	10, 12, 14	1	20 (508)	42 (1067)	42 (1067)	10 (254)	16 (406)	20 (508)	8 (203)	17 1/2 (445)	20 (508)

Dimensions are in inches (mm); Airflow CFM (L/s) and Product Information is Subject to Change Without Notice

* "A" Dim will increase or decrease 1" as the inlet diameter increases or decreases 2" from the standard inlet diameter.

** For Fan CFM @ a specific ESP see catalog for Fan Curves.

Notes: (☐ check if provided)

1. Available Options	2. Construction Details	2. Construction Details (Cont.)
☐ Reinforced foil covered fiberglass, no exposed edges ☐ Engineered polymer closed cell foam ☐ 1" Thick disposable filter and filter frame	- Units are manufactured with 22-gauge casing and 20-gauge inlet valve assembly - All insulations meet NFPA 90A and UL 181	- Standard insulation dual density, coated fiberglass, all exposed edges sealed - Flanged discharge - All insulation 1" (25.4mm)