


Tag:
Series : TL500

METAL*AIRE®
Submittal No: TL500-O-EH-SA

**Single Duct Air Terminal Low Profile With
Electric Heat and Integral Sound Attenuator**

Model: TL512 12" Oval Inlet
TL514 14" Oval Inlet
TL516 16" Oval Inlet



UNITS are manufactured with 20GA (1.0mm) Galvanized Steel Inlet Valve Assembly.

INSULATION: ☐ 1.5#/FT³ (24 Kg/m³) Dual Density, (4# Skin) (64 Kg/m³) Coated Fiberglass, All Exposed Edges Sealed

☐ 3#/FT³ (48 Kg/m³) Reinforced Foil Covered, Fiberglass. No Exposed Edges.

☐ Engineered Polymer Closed Cell Foam (No Fiberglass)

All Insulations Meet NFPA 90A and UL 181 for Erosion, Mold Growth, and 25/50 Flame Spread/Smoke Density Ratings, All Insulations are 1/2"

Model Number	Nominal Size	Dim. W x L	CFM Range	Width	Shipping Weight (Lbs)(Kg)
TL512	12 (Oval) (300)	10 (254) x 13 (330)	0-2200 (0-1.04)	18 (460)	59 Lbs (27 Kg)
TL514	14 (Oval) (350)	10 (254) x 16.25 (413)	0-3000 (0-1.42)	24 (610)	67 Lbs (30 Kg)
TL516	16 (Oval) (400)	10 (254) x 19.38 (492)	0-4000 (0-1.89)	28 (710)	77 Lbs (35 Kg)

Notes: (☐ check if provided)

1. Available Options	1. Available Options	2. Standard Construction Details
<input type="checkbox"/> 1" Fiberglass <input type="checkbox"/> 1/2" Foil Lined Fiberglass <input type="checkbox"/> 1" Foil Lined Fiberglass <input type="checkbox"/> 1" Thermopure <input type="checkbox"/> 1/2" Thermopure	<input type="checkbox"/> Engineered Polymer Foam <input type="checkbox"/> Slip & Drive Discharge Adapter <input type="checkbox"/> 20-Gauge Casing <input type="checkbox"/> Access Door <input type="checkbox"/> Metal Liner	<ul style="list-style-type: none">• 1/2" Fiberglass• Flush Discharge for Flanged Duct Connection• Units are manufactured with 22-gauge casing and 20-gauge inlet valve assembly• All insulations meet NFPA 90A and UL 181

Submittal No. TL500-O-EH-SA

Date: 06/16/2004

Dimensions are in inches

Page: 1 of 1