Tag:

Series: TL500

## METAL\*AIRE

**Submittal No: TL500-SA-HW** 

## Single Duct Air Terminal With Integral Sound Attenuator and Hot Water Coil

Models: TL506


6" Inlet

**TL508** 

8" Inlet

**TL510** 

10" Inlet



UNITS are manufactured with 20GA (1.0mm) Galvanized Steel Inlet Valve Assembly.

INSULATION: ☐ 1.5#/FT³ (24 Kg/m³) Dual Density, (4# Skin) (64 Kg/m³) Coated Fiberglass, All Exposed Edges Sealed

☐ 3#/FT³ (48 Kg/m³) Reinforced Foil Covered, Fiberglass. No Exposed Edges.

☐ Engineered Polymer Closed Cell Foam (No Fiberglass)

All Insulations Meet NFPA 90A and UL 181 for Erosion, Mold Growth, and 25/50 Flame Spread/Smoke Density Ratings, All Insulations are 1/2"

Model					Unit Weight with			
Number	Nominal Size	Height	Width	Dim. A	1R HW Coil	2R HW Coil	3R HW Coil	4R HW Coil
TL506	6 Dia. (152)	8 (203)	12 (305)	2 (51)	29 lbs 13 kg)	30 lbs (14 kg)	33 lbs (15 kg)	35 lbs (16 kg)
TL508	8 Dia. (203)	10 (254)	12 (305)	1 (25)	33 lbs (15 kg)	35 lbs (16 kg)	39 lbs (18 kg)	41 lbs (19 kg)
TL510	10 Dia. (254)	12 1/2 (318)	14 (356)	-	40 lbs (18 kg)	43 lbs (20 kg)	48 lbs (22 kg)	51 lbs (23 kg)

## Notes: (☐ check if provided)

1. Available Finishes	2. Construction Details	3. Construction Details (cont.)
Reinforced foil covered fiberglass, no exposed	Units are manufactured with 22-gauge casing	All insulation 1/2" (12.7 mm)
edges	and 20-gauge inlet valve assembly	
☐ Engineered polymer closed cell form	All insulations meet NFPA 90A and UL 181	
☐ Metal line	Standard insulation dual density, coated	
☐ Control panel covered	fiberglass, all exposed edges sealed	
☐ Flanged discharge	Slip and drive connections discharge standard	

Submittal No. TL500-SA-HW

Date: 06/16/2004

Dimensions are in inches

Page: 1 of 1