
GATE 1186 BRONZE

300 lb. SWP-1000 lb. WOG[†] • Heavy Duty Service Solid Wedge Disc • Non-Rising Stem Stainless Seat • Gland Packed • Union Bonnet • Threaded Ends

PATENTED

Wear-resistant stainless seat rings are securely expanded into the body to assure trouble-free service. Normal seating wear is restricted to the bronze wedge and can be easily replaced.



1186	Conforms to: MSS SP-80. Type 1,						
	Class 300, Threaded Ends.						
MATERIAL LIST							
NO.	PART	MATERIAL	SPECIFICATION				
1	Body	Bronze	ASTM B 61				
2	Bonnet	Bronze	ASTM B 61				
3	Wedge Disc	Bronze	ASTM B 61				
4	Stem	Bronze	ASTM B 61				
5	Stuffing Box	Bronze	ASTM B 16				
6	Union Bonnet Nut	Bronze	ASTM B 61				
7	Seat Ring	St. Steel	ASTM A 167				
8	Packing	Non-Asbestos	Commercial				
9	Gland	Bronze	ASTM B 16				
10	Packing Nut	Bronze	Commercial				
11	Handwheel	Mall. Iron	Commercial				
12	Handwheel Nut	Bronze	Commercial				
13	Identification Plate	Aluminum	Commercial				

DIMENSIONS - INCHES / MILIMETERS					
Units	Size	Α	В	С	
Inches	1/4	1 13/16	4 1/8	2 1/4	
MM	6.35	46.05	104.78	57.15	
Inches	3/8	1 7/8	4 1/8	2 1/4	
MM	9.53	47.63	104.78	57.15	
Inches	1/2	2 1/4	4 5/16	2 1/2	
MM	12.70	57.15	109.55	63.50	
Inches	3/4	2 1/2	4 9/16	2 3/4	
MM	19.05	63.50	115.90	69.85	
Inches	1	3	5 3/16	2 3/4	
MM	25.40	76.20	131.78	69.85	
Inches	1 1/4	3 3/8	5 15/16	3 1/4	
MM	31.75	85.73	150.83	82.55	
Inches	1 1/2	3 1/2	6 3/8	3 3/4	
MM	38.10	88.90	161.93	95.25	
Inches	2	3 3/4	7 11/16	4 1/4	
MM	50.80	95.25	195.28	107.95	

† Non-Shock



MILWAUKEE VALVE

The information presented on this sheet is correct at the time of publication. Milwaukee Valve reserves the right to change design, and/or material specifications without notice. For the most current information access www.milwaukeevalve.com

MMOVATION IN EVERY VALVE

SPECIFICATIONS