

GLOBE 592A

BRONZE

200 lb. SWP @ 550°F-400 lb. WOG† @ 150°F • Heavy Duty Service
Special Hardened S. S. Seat Ring and Disc • Union Bonnet
Gland Packed • Threaded Ends

- This valve has flat seat shutoff with plug type disc for throttling action and replaceable seat and disc.

SPECIFICATIONS

592A	Conforms to: MSS SP-80, Type 3, Class 200, Threaded Ends.
------	--

MATERIAL LIST


NO.	PART	MATERIAL	SPECIFICATION
1	Body	Bronze	ASTM B 61
2	Bonnet	Bronze	ASTM B 61
3	Bonnet Nut	Bronze	ASTM B 61
4	Stuff Nut	Bronze	ASTM B 62
5	Stem	Bronze	ASTM B 61
6 ¹	Disc Ring	Bronze	ASTM B 62
7	Seat Ring	St. Steel	ASTM A 276, TY. 420
8	Disc	St. Steel	ASTM A 276, TY. 420
9	Gland	Brass	ASTM B 16
10	Wheel Nut	Brass	ASTM B 16
11	Handwheel	Mall. Iron	Commercial
12	Packing	Non-Asbestos	
13	Name Plate	Sh. Alum.	Commercial

¹ Not shown - used on 1 1/4" and larger valves only.

DIMENSIONS - INCHES / MILLIMETERS

Units	Size	A	B	C
Inches	1/4	2 1/8	4 3/8	2
MM	6.35	53.98	111.13	50.80
Inches	3/8	2 3/8	4 7/16	2
MM	9.53	60.33	112.73	50.80
Inches	1/2	2 1/2	4 1/2	2 1/2
MM	12.70	63.50	114.30	63.50
Inches	3/4	2 15/16	5 1/8	2 3/4
MM	19.05	74.61	130.18	69.85
Inches	1	3 3/8	5 1/4	3 1/4
MM	25.40	85.73	133.35	82.55
Inches	1 1/4	3 7/8	6 3/16	3 3/4
MM	31.75	98.43	157.18	95.25
Inches	1 1/2	4 1/2	7 1/4	4 1/4
MM	38.10	114.30	184.15	107.95
Inches	2	4 7/8	8 3/16	4 3/4
MM	50.80	123.83	207.98	120.65

† Non-Shock



INNOVATION IN EVERY VALVE



MILWAUKEE VALVE

The information presented on this sheet is correct at the time of publication. Milwaukee Valve reserves the right to change design, and/or material specifications without notice. For the most current information access www.milwaukeevalve.com

www.milwaukeevalve.com