



MODEL ACSLJ-6 *FORMED STATIONARY ACOUSTICAL* *STRAIGHT BLADE*

Standard Construction:


- Frame:** 6" (152 mm) x 16 ga. galvanized steel.
- Blades:** 20 ga. galvanized steel, 22 ga. perforated, approximately 6" (152 mm) on centers.
- Blade Fill:** 6 lb. per cubic foot density mineral wool.
- Blade Angle:** 45°
- Screen:** Bird screen - 1/2" x 1/2" (12.7 mm x 12.7 mm) x 19 ga. galvanized steel, in a removable frame on interior of louver.
- Finish:** Mill galvanized.
- Minimum Size:** 12"w x 16"h (304 mm x 406 mm)
- Maximum Section Size:** 60"w x 96"h (1524 mm x 2438 mm)

Options:

- Screens:** Insect screen - 18 x 16 mesh aluminum.
 Other: _____
- Finish:** Prime Coat.
 Baked enamel.
 Kynar 500 Enamel.
 Other: _____

Sill Extensions:


- Flange:** 1-1/2" (38 mm) (front or rear)
- Material:** Various materials and gauges
- Notes:** Louvers fabricated 1/4" (6.4 mm) under opening size unless otherwise noted.




Channel Frame

FREE-FIELD NOISE REDUCTION IN DECIBLES SELECTED 1/3 OCTAVE BANDS CENTER FREQUENCY HZ							
HZ	100	125	250	500	1000	2000	4000
db	13	10	10	13	19	24	19

Acoustical Performance was determined by Riverbank Acoustical Laboratories, per ASTM E 90-97 "Recommended Practice for Laboratory Measurement of Airborne Sound Transmission loss of Building Partitions" and E 413-87 "Standard Classification for Determination of Sound Transmission Class."



Visible Mullion



Sill Extension

Flange Frame

Specifications are correct at time of printing. However, as part of our 'continuous improvement program,' we reserve the right to make further improvements without notice.
 © JULY, 2000 NCA Manufacturing

Project:
 Location:
 Architect:
 Engineer:

Contractor:
 Address:
 P.O. Number:
 Date:



*MODEL ACSLJ-6
FORMED STATIONARY ACOUSTICAL
STRAIGHT BLADE*


© JULY, 2000 NCA Manufacturing

Specifications


Furnish and install where shown model **ACSLJ-6** louver, manufactured by **NCA Manufacturing**. Louver blades shall be **acoustical** on a **45** degree angle with 6 lb. per cubic foot mineral wood filler between 20 gauge galvanized face and 22 gauge galvanized perforated. Frame shall be **6"** deep 16 gauge galvanized. Screen shall consist of 1/2" mesh 19 gauge galvanized in removable frame mounted on interior. Louver shall be finished with Polyurethane Enamel, Kynar 500, or another finish selected from NCA's standard color chart. Louvers shall be tested per AMCA standard 511 for water and air and ASTM E 90-97 for acoustics, and perform as per data on this sheet.

ACSLJ-6 Free Area for 48 x 48 louver is 3.97 sq. ft. (24.8%)

ACSLJ-6 - 02-05



**PRESSURE DROP
INTAKE**



Water Penetration

Water Penetration Data applies to test unit size 48" x 48" only. Beginning of Water Penetration is 970 FPM Free Area Velocity.

Performance shown is at standard air density 0.075 lbs./ft³.