



*MODEL FD GARBAGE CHUTE FIRE DAMPER
STATIC FIRE DAMPER
FOR HORIZONTAL MOUNTING*


MODEL: RHC-GC-80



LISTED AND LABELLED BY:



DESIGNED AND TESTED IN ACCORDANCE WITH UL-555 AND ULC-S112. MEETS ALL NFPA-90A REQUIREMENTS FOR FIRE DAMPERS.



PATENT APPLIED FOR

NOTE:

This is a specially designed, spring loaded horizontal fire damper complete with over-sized housing & round collar for garbage chute applications. The damper has 100% free area.

OPTIONS:

- Electro thermal links
- Other fusible links 212°F.

“These Dampers are UL/ULC Approved For Use in Static Systems Where The Fan Shuts Down in the Event of a Fire.”

STANDARD SIZES: (Others on request)

Diameter	Overall Size
20" (508mm)	26" w x 27" h
24" (610mm)	30" w x 32" h

Manufacturer's Recommendations

All moving parts of the damper must be inspected and cycled at intervals not greater than every six months and in accordance with the latest edition of NFPA 90A, 92A, local codes and the actuator manufacturer. In addition, fuse links shall be removed and inspected for corrosion. Dry lubricants are recommended.

Specifications are correct at time of printing. However, as part of our 'continuous improvement program,' we reserve the right to make further improvements without notice.

© 1999 NCA Manufacturing

FD-GC - 02-05

Project:

Contractor:

Location:

Address:

Architect:

P.O. Number:

Engineer:

Date: