



MODEL XAD-6-GL **EXTRUDED ALUMINUM LOUVER** **DRAINABLE BLADE. AMCA LICENSED.**



Standard Construction:

- Frame:** 6" x .081 (152 mm x 2.1 mm) extruded aluminum (6063-T5).
- Blades:** .081 (2.1 mm) extruded aluminum (6063-T5), approximately 5" (127 mm) on centers.
- Blade Angle:** 37-1/2°
- Screen:** Bird screen - 3/4" x .050 (19 mm x 12.7 mm) flattened expanded aluminum in a removable frame on interior of louver.
- Finish:** Mill aluminum.
- Minimum Size:** 12"w x 12"h (304 mm x 304 mm)
- Maximum Size:** 96"w x 96"h (2438 mm x 2438 mm)


Options:

- Screens:** Insect screen - 18 x 16 mesh aluminum
1/2" x .063 (12.7 mm x 1.6 mm) aluminum.
Other - _____
- Finish:** Prime Coat
Baked Enamel
Kynar
Powder Coat
Clear Anodize - 204-R1 and 215-R1
Integral Color Anodize
Other - _____



Sill Extensions:

- Flange:** 1-1/2" (38 mm) (front or rear)
- Frame:** .125 (3.2 mm) Extruded Aluminum
- Blade:** .125 (3.2 mm) Extruded Aluminum

Notes: Louvers fabricated 1/4" (6.4 mm) under opening size unless otherwise noted.



Channel Frame



Specifications are correct at time of printing. However, as part of our 'continuous improvement program,' we reserve the right to make further improvements without notice.

© JULY, 2000 NCA Manufacturing

Project:

Contractor:

Location:

Address:

Architect:

P.O. Number:

Engineer:

Date:



MODEL XAD-6-GL EXTRUDED ALUMINUM LOUVER DRAINABLE BLADE. AMCA LICENSED.

PERFORMANCE DATA


© JULY, 2000 NCA Manufacturing

Specifications

Furnish and install where shown model **XAD-6-GL** louver, manufactured by **NCA Manufacturing**. Louvers shall be the stationary **drainable** type with a frame depth of **6 inches**. Frames and blades shall be .081 inches thick 6063-T5 extruded aluminum alloy. Blades shall be located on a **37-1/2** degree blade angle. Screens shall consist of 3/4" expanded aluminum, with an extruded frame, mounted to the louver interior, and be removable for cleaning. Louvers shall be finished with Polyurethane Acrylic enamel, Kynar 500, Anodize or other finishes selected by the architect from NCA standard color charts.


XAD-6-GL FREE AREA IN SQ. FT.

	Width - Inches														
	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96
12	0.23	0.38	0.54	0.69	0.84	0.99	1.15	1.30	1.45	1.61	1.76	1.91	2.06	2.22	2.37
18	0.43	0.72	1.00	1.29	1.58	1.87	2.15	2.44	2.73	3.01	3.30	3.59	3.88	4.16	4.45
24	0.63	1.05	1.47	1.90	2.32	2.74	3.16	3.58	4.00	4.42	4.84	5.27	5.69	6.11	6.53
30	0.83	1.39	1.94	2.50	3.05	3.61	4.17	4.72	5.28	5.83	6.39	6.94	7.50	8.05	8.61
36	1.03	1.72	2.41	3.10	3.79	4.48	5.17	5.86	6.55	7.24	7.93	8.62	9.31	10.00	10.69
42	1.44	2.39	3.35	4.31	5.27	6.23	7.18	8.14	9.10	10.06	11.02	11.97	12.93	13.89	14.85
48	1.64	2.73	3.82	4.91	6.01	7.10	8.19	9.28	10.37	11.47	12.56	13.65	14.74	15.84	16.93
54	1.84	3.07	4.29	5.52	6.74	7.97	9.20	10.42	11.65	12.88	14.10	15.33	16.55	17.78	19.01
60	2.04	3.40	4.76	6.12	7.48	8.84	10.20	11.56	12.92	14.28	15.64	17.01	18.37	19.73	21.09
66	2.24	3.74	5.23	6.73	8.22	9.71	11.21	12.70	14.20	15.69	17.19	18.68	20.18	21.67	23.17
72	2.44	4.07	5.70	7.33	8.96	10.59	12.22	13.84	15.47	17.10	18.73	20.36	21.99	23.62	25.25
78	2.64	4.41	6.17	7.93	9.70	11.46	13.22	14.98	16.75	18.51	20.27	22.04	23.80	25.56	27.33
84	3.05	5.08	7.11	9.14	11.17	13.20	15.23	17.27	19.30	21.33	23.36	25.39	27.42	29.45	31.48
90	3.25	5.41	7.58	9.74	11.91	14.08	16.24	18.41	20.57	22.74	24.90	27.07	29.23	31.40	33.56
96	3.45	5.75	8.05	10.35	12.65	14.95	17.25	19.55	21.85	24.15	26.45	28.74	31.04	33.34	35.64



NCA Manufacturing, Inc. certifies that the Model XAD-6-GL louver shown herein is licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings program.

The AMCA Certified Ratings Seal applies to air performance ratings and water penetration ratings only.



SEPTEMBER, 2004