

DRIPPERLINE

FITTINGS AND ACCESSORIES

Applications

- Fits Techline® CV, Techline® and Techlite® Dripperlines

Features/Benefits

- Barbed fittings for secure fit and easy installation without glue or tools
- Maximum recommended system pressure: 50 psi; 8mm fittings: 25 psi
- UV resistant
- Durable one-piece construction
- Allows for easy on-site inspection of proper fitting installation

8mm TECHLITE FITTINGS



SLCOUP
Insert Coupling



SLTEE
Insert Tee



SL050FA
1/2" Female Adapter



SL050FTEE
1/2" Female Combination Tee



END CAP*



8mm Techlite can be attached to blank Techline tubing.

*End Cap can be made from Techline CV, Techline or 17mm Techlite Dripperline by folding 8mm Techlite tubing over twice and sliding 1 1/4" cut section over the end.

TECHLINE CV, TECHLINE and 17mm TECHLITE FITTINGS



TLCOUP
Insert Coupling



TLELL
Insert Elbow



TLTEE
Insert Tee



TLCROS
Insert Cross



TL050MA
1/2" Male Adapter



TL075MA
3/4" Male Adapter



TL075FTEE
Combination Tee
Ins x Ins x 3/4" FPT



TL2W075MA
3/4" MPT
"V" 2-Way Insert



TLIAPE-B
Insert Adapter for
1" or Larger PE
(requires 11mm or 7/16" punch)



TLIAPVC-B
Insert Adapter
with Grommet for
1 1/2" or Larger PVC
(requires TDBIT16.5)



TDBIT16.5
Drill bit for PVC –
TLIAPVC



TLFIG8
Figure 8 Line End



TLDPLUG
Dripper Plug Ring



TLMTUBEADP
Drifter Micro-Tubing
Adapter



TLS6
6" Soil Staple
(Place approximately every
3' of tubing, plus two on
each tee, elbow or cross.)



TLSOV
Shut-Off Valve
Ins x Ins



TLCV
Inline Check Valve
0.9-4.4 GPM
Closing Pressure
5.7 psi
Opening Pressure
7.1 psi

FPT = Female Pipe Thread
MPT = Male Pipe Thread
Ins x Ins = Insert by Insert