



Pure-Core® Blue Submittal and Data Sheet

August 2000

P.R. 200 PSI - SDR 7 - Mandarin Tag Color

Nominal Pipe Size (inches)	Approximate Outside Diameter (inches)	Average Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')
¾	1.07	0.824	0.118	15
1	1.37	1.049	0.150	25
1¼	1.80	1.380	0.197	43
1½	2.10	1.610	0.230	59

P.R. 200 PSI - SDR 9 - White Tag Color (CTS)

Nominal Pipe Size (inches)	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')
½	0.625	0.47	0.069	5
¾	0.875	0.66	0.097	10
1	1.125	0.85	0.125	17
1¼	1.375	1.04	0.153	26
1½	1.625	1.23	0.181	36
2	2.125	1.62	0.236	62

General Notes:

1. SDR 7 pipe meets the requirements of ASTM D 2239 and AWWA C901.
2. SDR 9 tubing meets the requirements of ASTM D 2737 and AWWA C901 with Copper Tube Size (CTS) outside diameters.
3. Material is high-density PE 3408 meeting cell class 345464.
4. Products meet the requirements of ANSI/NSF 61 for potability and are listed to ANSI/NSF 14.
5. Color-coded tags denote product and pressure rating for improved warehouse control.
6. Approximate weights are for estimating purposes only.
7. All orders are subject to final acceptance by PW Pipe sales management.