



Drain Line (Perforated or Solid) Submittal and Data Sheet

August 2000

Perforated or Solid

Nominal Pipe Size (inches)	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')	Length per Crate (feet)	Approximate Crate Weight (lbs)
3	3.250	3.10	0.070	47	950	450
4	4.215	4.05	0.075	66	900	590
6	6.275	6.06	0.100	130	390	510

General Notes:

1. Solid 3", 4", and 6" pipe and perforated 4" pipe conform to ASTM D 2729 and are tested by to the requirements of the Uniform Plumbing Code™.
2. Holes in perforated pipe are ½ inch in diameter, 5 inches on center and are provided in two rows. Rows are parallel to the pipe axis and 120° apart.
3. Proper hole positioning is assured by centering pipe printline at top.
4. Pipe material conforms to ASTM D 1784 cell class 12364 or 12454.
5. All pipe has integral solvent-weld bell ends.
6. All pipe is produced in 10-foot lengths standard.
7. Inside diameters may vary due to allowable manufacturing tolerances.
8. Approximate weight values are for estimating purposes only.
9. All orders are subject to final acceptance by PWPipe sales management.