



Eagle Tri-Stripe® Gas Pipe and Tubing Submittal and Data Sheet

August 2000

Tri-Stripe Pipe - P.R. 100 PSI

Nominal Pipe Size (inches)	DR	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')
½	9.33	0.840	0.64	0.090	9
¾	11	1.050	0.84	0.095	13
1	11	1.315	1.06	0.119	20
1¼	11	1.660	1.33	0.151	31
1½	11	1.900	1.53	0.173	41
2	11	2.375	1.91	0.216	64
3	11	3.500	2.81	0.318	140
4	11	4.500	3.62	0.409	230
6	11	6.625	5.33	0.602	500

Tri-Stripe Tubing - P.R. 100 PSI (CTS)

Nominal Pipe Size (inches)	DR	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')
½	7	0.625	0.43	0.090	7
1	11	1.125	0.90	0.102	14

Tri-Stripe Tubing - P.R. 90 PSI (CTS)

Nominal Pipe Size (inches)	DR	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')
1	12.5	1.125	0.93	0.090	13

General Notes:

1. Eagle Tri-Stripe gas pipe and tubing meets the requirements of ASTM D 2513.
2. Material is high-density PE 3408 meeting cell class 345464C.
3. Inside diameters may vary due to allowable manufacturing tolerances.
4. Approximate weights are for estimating purposes only.
5. All orders are subject to final acceptance by PWPipe sales management.