



Precision Plumbing Products

**LOW LEAD**

**MINI-PRIME  
BATTERY OPERATED TRAP PRIMER**

www.pppinc.net

**MINI-PRIME W/BOX**  
MPB-500-12V



**ROUGH-IN  
DIMENSIONS**  
A. 12" INCHES  
B. 12" INCHES  
Depth 3 3/8" INCHES

(cover not shown in photo).

**MINI-PRIME**  
MP-500-12V



**INLET:** 1/2" NPT Male. ANSI/ASME B1.20.1.

**OUTLET:** 1/2" NPT Female. ANSI/ASME B1.20.1

**WATER DISTRIBUTION:** Distribution Units (DU Series) Drain Outlet: 5/8" OD and 1/2" OD Compression Fittings SAEJ512 1/2" female NPT ANSI/ASME B1.20.1.

**SOLDER JOINTS:** 95.5% lead free. Containing lead not in the excess of 0.2%.

**ELECTRICAL COMPONENTS:** Test Switch, Timer Solenoid Valve UL Listed.

**TEMPERATURE/PRESSURE:** 32 F-125 F, 20 PSI - 150 PSI. Minimum 2 oz. water at 20 PSI. per drain served.

**ACCESS DOOR FOR MP-500 12V Model:** D-814PC, D-814SS, F-814PC, F-814SS.

**RECYCLE TIMER BOX:** Dimensions - (L) 7 5/8" x (W) 4 5/8" x (D) 2 3/8"

**PROJECT SUBMITTAL**

Project: \_\_\_\_\_

Contractor: \_\_\_\_\_

Engineer: \_\_\_\_\_

Date Submitted: \_\_\_\_\_

Prepared By: \_\_\_\_\_

**NOTE:**

**DESIGNED FOR USE WITH 1 TO 4 FLOOR DRAINS. DISTRIBUTION UNITS PURCHASED SEPARATELY.**

**THE PRIMING VALVE MUST HAVE A MINIMUM ELEVATION OF 12 INCHES (305MM) ABOVE THE FINISHED FLOOR.**



JL Industries, Inc.

**Precision Plumbing Products**

Division of JL Industries, Inc.

Airport Business Center  
6807 NE 79th Court, Suite E  
Portland, Oregon 97218

T (503) 256-4010

F (503) 253-8165

www.pppinc.net

US PATENT NUMBER 5,797,419

CANADIAN PATENT NUMBER 2,174,578

