

TECH SPECS

Poly Pipe Saddle Tee

Saves time, minimizes excavation for head replacements as well as new system installs. The ratchet locking saddle wraps easily and securely around poly pipe with minimal clearance. The easy-grip piercing cap is then twisted and locked into position for a leaktight connection and optimal water flow.

Features

- Engineered to pierce and seal heavy-wall 1" (25.4 mm) poly pipe
- Positive locking to provide a rock-solid connection, even in extreme climates
- Requires less digging and less installation time – than all other saddle tees
- Auto-alignment of flow ports maximizes available pressure for enhanced irrigation performance
- Nearly indestructible design and materials reduce chance of callbacks
- Available with 1/2" (12.7 mm) NPT and 3/4" (19.0 mm) NPT piercing caps for connections

Specifications

- Operating pressure up to 80 PSI (5,5 Bars), and 110° F (43° C)
- All components made of high-strength materials – won't crack or lose pressure over time

Models

- A11245 Ratcheting Saddle w/ 1/2" (12.7 mm) Piercing Cap
- A11250 Ratcheting Saddle w/ 3/4" (19.0 mm) Piercing Cap

Rain Bird Corporation

6991 East Southpoint Road, Tucson, AZ 85706, U.S.A. Phone: (520) 741-6100 Fax: (520) 741-6522

Rain Bird Corporation

970 West Sierra Madre Avenue, Azusa, CA 91702, U.S.A. Phone: (626) 812-3400 Fax: (626) 812-3411

Rain Bird International, Inc.

P.O. Box 37, Glendora, CA 91740-0037, USA Phone: (626) 963-9311 Fax: (626) 852-7343

Technical Service and Support

(800) RAINBIRD (U.S. and Canada only)

Specification Hotline

(800) 438-3005 (U.S. and Canada only)

www.rainbird.com

The Intelligent Use of Water™ – Visit www.rainbird.com to learn about our efforts







