

Efficiency Series

Model

ST-2020-1.28

ADA Compliant Vitreous China Water Closet

DESCRIPTION

Complete ADA compliant vitreous china water closet.

Flush Cycle

Model ST-2020-1.28 (1.28 gpf/4.8 Lpf)





SPECIFICATIONS

Water Closet


- Vitreous china
- · Floor mounted
- ADA Compliant
- Siphon jet flushing action
- 1.5" I.P.S. top spud inlet
- · 2" trapway diameter
- Fully glazed trapway
- Toilet seat not included
- Integral flushing rim
- Elongated bowl
- Water spot area 10" x 7 1/2"
- Closet bolts and caps included
- ASME A112.19.2/CSA B45.1


Colors/Finishes

White

Recommended Accessories

Compatible with toilet seat models:
 Olsonite 10CT
 Bemis 1955 CT
 Church Commercial 295CT





Product Specification

Elongated water closet shall be made of vitreous china with a 1.5" top spud. Bowl shall be ADA compliant when installed at required height of 17" from floor to top of fixture. Water closet shall be floor mounted. Water Closet shall use 1.28 gpf / 4.8 Lpf. Water Closet shall be Sloan Model ST-2020-1.28.

Meets the American Disabilities Guidlines and ANSI A117.1 requirements when installed according to these requirements.



NOTE:

Plumbing System Requirements

√ Minimum Flowing Pressure: 25 PSI

√ Minimum Flow Rate: 18 GPM

This space for Architect/Engineer approval	
Job Name	Date
Model Specified	Quantity
Variations Specified	
Customer/Wholesaler	
Contractor	
Architect	





certificates to meet 100% of the company's purchased electricity use at its Franklin Park, Illinois facility.

SLOAN

Sloan Valve Company 10500 Seymour Avenue, Franklin Park, IL 60131 Phone: 1-800-9-VALVE-9 (982-5839) or 1-847-671-4300 Fax: 1-800-447-8329 or 1-847-671-4380 www.sloanvalve.com

Copyright © 2009 Sloan Valve Company 08/09 Rev. 0