

Model ST-2052-1.6/1.1 Dual Flush Vitreous China Water Closet

DESCRIPTION

Complete Dual Flush Vitreous China Wall Hung Water Closet.

Flush Cycle

Model ST-2052 Dual Flush Wall Mount (Full Flush 1.6 gpf/6.0 Lpf, Reduced Flush 1.1 gpf/4.2 Lpf)





SPECIFICATIONS

Water Closet


- Dual flush
- Wall hung vitreous china
- · Elongated bowl
- Siphon jet flushing action
- 1.5" I.P.S. top spud inlet
- 2" fully glazed trapway diameter
- · Mounting hardware, carrier and toilet seat not Included
- Integral flushing rim
- Water spot area 9 1/2" x 8 1/4"
- ASME A112.19.2/CSA B45.1

Colors/Finishes


• White

Recommended Accessories

· Compatible with toilet seat models: Olsonite 10CT Bemis 1955 CT Church Commercial 295CT



FINISHED FLOOR



Product Specification

Elongated wall hung water closet shall be made of vitreous china with a 1.5" top spud. Bowl shall be ADA compliant when installed at required height of 17"-19" from floor to top of fixture. Water Closet shall be dual flush 1.6 / 1.1 gpf. Water Closet shall be Sloan Model ST-2052-1.6/1.1.

Meets the American Disabilities Guidlines and ANSI A117.1 requirements when installed according to these requirements.



NOTE: Plumbing System Requirements √ Minimum Flowing Pressure: 25 PSI √ Minimum Flow Rate: 18 GPM

This space for Architect/Engineer approval		
Job Name	Date	
Model Specified	Quantity	
Variations Specified		
Customer/Wholesaler		
Contractor		
Architect		
The information contained in this document is subject to change without notice.		



Sloan Valve Company is buying renewable energy certificates to meet 100% of the company's purchased electricity use at its Franklin Park, Illinois facility.



Sloan Valve Company 10500 Seymour Avenue, Franklin Park, IL 60131 Phone: 1-800-9-VALVE-9 (982-5839) or 1-847-671-4300 Fax: 1-800-447-8329 or 1-847-671-4380 www.sloanvalve.com

Copyright © 2009 Sloan Valve Company Printed in the U.S.A. Rev. 0a (09/09)