AUTOMATIC GLOBE VALVES

MODEL 3100

Master Valve Normally Open, Electric

Available in 3/4", 1", 1 ½", 2", 2 ½" & 3"

The Model 3100 performs in the opposite manner of a normally closed electric valve with electricity required to close the valve rather than open it. During the time the solenoid is not energized, the Model 3100 will remain open.

FEATURES

- Normally open design.
- Solid brass construction.
- Water-proof solenoid coil, guaranteed for the life of the valve.
- Self-cleaning orifice.
- Diaphragm of one-piece molded construction with integral O-ring seal reinforced with 600 lb. test fabric.
- Cross handle flow control standard on 1" through 3" sizes, optional on ³/₄" size.
- Slow closing. No water hammer, surge or noise.
- Will operate on pressure up to 200 psi for 3/4†through 2†sizes and 150 psi. for 21/2†and 3†sizes.
- 24 VAC 3-way solenoid.

OPTIONAL THREADS

Available with British Standard Pipe Threads.

OPTIONAL SOLENOIDS

- 24 VAC, 110 VAC and 220 VAC conduit mount.
- 12 VDC
- Other types available. Contact factory for information.

GUARANTEE

Superior Controls Co., Inc. guarantees the Model 3100 Series Automatic Electric Diaphragm Globe Valves against defective parts and workmanship for THREE YEARS.

The 600 pound test diaphragm is guaranteed for FIFTEEN YEARS.

The water-proof solenoid coil is guaranteed FOR THE LIFE OF THE VALVE.