

QuickVic® Rigid Coupling for Steel

STYLE 107H

The patented Style 107H rigid coupling joins 2 – 8" / 50 – 200 mm standard roll grooved and cut grooved steel pipe.* The joint is assembled without disassembling the bolts, nuts, gasket and housings. The Style 107H coupling requires lubrication only be applied to the sealing lips of the gasket before sliding the coupling on pipe grooved to Victaulic specifications. Refer to Victaulic Field Installation Handbook I-100 for required steps.

The Style 107H provides rigidity with its angle bolt pad design and accommodates up to 750 psi/5170 kPa depending on pipe wall thickness. The Style 107H is rigid and does not accommodate expansion, contraction or angular deflection. Support and hanging requirements correspond to ASME B31.1 Power Piping Code and ASME B31.9 Building Services Piping Code.

* Sizes 2-4" / 50-100 mm may be used to join 304/304L and 316/316L Schedule 10 stainless steel pipe with a maximum rated working pressure of 300 psi/2065 kPa.



PATENTED

MATERIAL SPECIFICATIONS

Housing: Ductile iron conforming to ASTM A-536, grade 65-45-12. Ductile iron conforming to ASTM A-395, grade 65-45-15, is available upon special request.

Housing Coating: Orange enamel.

Optional Coatings:

- Hot dipped galvanized

Gasket:

- **Grade "EHP"**

EHP (Red stripe color code) Temperature range –30°F to +250°F/–34°C to +121°C.

Recommended for hot water service within the specified temperature range plus a variety of dilute acids, oil-free air and many chemical services.* UL classified in accordance with ANSI/NSF 61 for cold +86°F/+30°C and hot +180°F/+82°C potable water service. NOT RECOMMENDED FOR PETROLEUM SERVICES.

- **Grade "T" nitrile**

Nitrile (Orange color code). Temperature range –20°F to +180°F/–29°C to +82°C.

Recommended for petroleum products, air with oil vapors, vegetable and mineral oils within the specified temperature range. Not recommended for hot water services over +150°F/+66°C or for hot dry air over +140°F/+60°C.

* Services listed are General Service Recommendations only. It should be noted that there are services for which these gaskets are not recommended. Reference should always be made to the latest Victaulic Gasket Selection Guide for specific gasket service recommendations and for a listing of services which are not recommended.

Bolts/Nuts: Heat-treated plated carbon steel, trackhead meeting the physical and chemical requirements of ASTM A-449 and physical requirements of ASTM A-183.

JOB/OWNER

System No. _____

Location _____

CONTRACTOR

Submitted By _____

Date _____

ENGINEER

Spec Sect _____ Para _____

Approved _____

Date _____

www.victaulic.com

VICTAULIC IS A REGISTERED TRADEMARK OF VICTAULIC COMPANY. © 2009 VICTAULIC COMPANY. ALL RIGHTS RESERVED.

REV_A




06.21_1


QuickVic® Rigid Coupling for Steel

STYLE 107H

DIMENSIONS



**STYLE 107H PRE-ASSEMBLED
(INSTALLATION-READY CONDITION)**



STYLE 107H JOINT ASSEMBLED

Size		Allow. Pipe End Sep. †	© Bolt/Nut	Dimensions – Inches/mm					Aprx. Wgt. Ea.
Nominal Size Inches/ mm	Actual Outside Diameter Inches/ mm	Inches/ mm	No. - Size Inches/ mm	Pre-assembled (Installation-ready condition)		Joint Assembled			Lbs./ kg
				X	Y	X	Y	Z	
2 50	2.375 60.3	0.15 3.8	2 – 3/8 x 2 1/2 M10 x 2 1/2	3.87 98.3	5.75 145.9	3.63 92.3	5.63 142.9	1.97 50.0	2.1 0.95
2 1/2 65	2.875 73.0	0.15 3.8	2 – 3/8 x 2 1/2 M10 x 2 1/2	4.37 111.0	6.26 159.1	4.15 105.5	6.15 156.3	1.97 50.0	2.5 1.1
3 80	3.500 88.9	0.15 3.8	2 – 1/2 x 3 M12 x 3	4.95 125.7	7.36 186.8	4.71 119.8	7.24 184.0	1.97 50.0	3.1 1.4
4 100	4.500 114.3	0.15 3.8	2 – 1/2 x 3 M12 x 3	5.97 151.6	8.39 213.2	5.73 145.6	8.29 210.4	2.04 51.8	3.9 1.8
5 125	5.563 141.3	0.15 3.8	2 – 1/2 x 3 M12 x 3	7.17 182.1	9.72 246.9	6.96 176.9	9.63 244.6	2.09 53.1	5.1 2.3
6 150	6.625 168.3	0.15 3.8	2 – 5/8 x 3 1/4 M16 x 3 1/4	8.31 211.1	11.32 287.5	8.13 206.6	11.23 285.3	2.04 51.8	6.8 3.1
8 200	8.625 219.1	0.22 5.6	2 – 5/8 x 4 M16 x 4	10.57 268.6	13.56 344.3	10.32 262.2	13.44 341.3	2.55 64.8	10.5 4.7

† The allowable pipe separation dimension shown is for system layout purposes only. Style 107H QuickVic rigid couplings are considered rigid connections and will not accommodate expansion or contraction of the piping system.

@ Number of bolts required equals number of housing segments.

WARNING: Depressurize and drain the piping system before attempting to install, remove or adjust any Victaulic piping products.

QuickVic® Rigid Coupling for Steel

STYLE 107H

PERFORMANCE

ANSI STANDARD

Size		Schedule 10			Schedule 40		
Nominal Inches/ mm	Actual Outside Diameter Inches/ mm	Wall Thick. Inches/ mm	Max. * Joint Work. Press. psi/kPa	Max. * Permis. End Load Lbs./N	Wall Thick. Inches/ mm	Max. * Joint Work. Press. psi/kPa	Max. * Permis. End Load Lbs./N
2 50	2.375 60.3	0.109 2.77	600 4135	2658 11823	0.154 3.91	750 5170	3323 14780
2½ 65	2.875 73.0	0.120 3.05	600 4135	3895 17325	0.203 5.15	750 5170	4869 21658
3 80	3.500 88.9	0.120 3.05	600 4135	5773 25680	0.216 5.49	750 5170	7216 32098
4 100	4.500 114.3	0.120 3.05	500 3450	7952 35372	0.237 6.02	750 5170	11928 53058
5 125	5.563 141.3	0.134 3.4	500 3450	12153 54060	0.258 6.55	750 5170	18229 81086
6 150	6.625 168.3	0.134 3.40	500 3450	17236 76670	0.280 7.11	700 4825	24130 107335
8 200	8.625 219.1	0.148 3.76	300 2070	17528 77970	0.322 8.18	600 4135	35056 155936

* Working Pressure and End Load are total from all internal and external loads grooved in steel pipe in accordance with Victaulic specifications. Contact Victaulic for performance on other pipe.

WARNING: FOR ONE TIME FIELD TEST ONLY, the Maximum Joint Working Pressure may be increased to 1 ½ times the figures shown.

DIN STANDARD

Size		Normal DIN Wall Pipe			Other DIN Wall Pipe		
Nominal Inches Actual mm	Actual Outside Diameter Inches mm	Wall Thick. Inches mm	Max. * Joint Work. Press. psi/kPa	Max. * Permis. End Load Lbs./N	Wall Thick. Inches mm	Max. * Joint Work. Press. psi/kPa	Max. * Permis. End Load Lbs./N
2 50	2.375 60.3	0.091 2.3	600 4135	2658 11823	0.157 4.0	750 5170	3323 14780
3 80	3.500 88.9	0.114 2.9	600 4135	5773 25680	0.197 5.0	750 5170	7216 32098
4 100	4.500 114.3	0.126 3.2	500 3450	7952 35372	0.220 5.6	750 5170	11928 53058
6 150	6.625 168.3	0.157 4.0	500 3450	17236 76670	0.280 7.1	700 4825	24130 107335
8 200	8.625 219.1	0.177 4.5	300 2070	17528 77970	0.315 8.0	600 4135	35056 155936

* Working Pressure and End Load are total from all internal and external loads grooved in steel pipe in accordance with Victaulic specifications. Contact Victaulic for performance on other pipe.

WARNING: FOR ONE TIME FIELD TEST ONLY, the Maximum Joint Working Pressure may be increased to 1 ½ times the figures shown.

QuickVic® Rigid Coupling for Steel

STYLE 107H

GENERAL NOTES

NOTE: When assembling Style 107H QuickVic rigid couplings onto end caps, take additional care to make certain the end cap is fully seated against the gasket end stop. For Style 107H QuickVic rigid couplings, use Victaulic No. 60 end caps containing the “QV” or “QV/EZ” markings on the inside face. Victaulic No. 460-SS stainless steel endcaps shall not be used with Style 107H QuickVic rigid couplings. Non-Victaulic fittings shall not be used with Style 107H QuickVic rigid couplings.

INSTALLATION

Reference should always be made to the I-100 Victaulic Field Installation Handbook. Installation instructions are included with each shipment of Victaulic products and are available in PDF format on our website at www.victaulic.com.

WARRANTY

Refer to the Warranty section of the current Price List or contact Victaulic for details.

NOTE

This product shall be manufactured by Victaulic or to Victaulic specifications. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.

For complete contact information, visit www.victaulic.com

06.21 5916 REV A UPDATED 10/2009

VICTAULIC IS A REGISTERED TRADEMARK OF VICTAULIC COMPANY. © 2009 VICTAULIC COMPANY. ALL RIGHTS RESERVED.

06.21

