


Chilled Water Buffer Tank



	Performance Limitations				
Construction					
Carbon Steel	Max Design Temp: 450F				
Exterior Primer Painted	Max Design Press: 125 PSI				

				Center-line Height (A in inches) for various Connection						on	
MODEL	GAL	(IN.)	(IN.)	2"NPT	2 1/2"	3" FLG	4" FLG	6" FLG	8" FLG	10" FLG	12" FLG
AWCBT-120	120	24	60	12	12.25	12.50	13	14	15	16	17
AWCBT-200	200	30	72	14	14.25	14.50	15	16	17	18	19
AWCBT-300	300	36	72	15.75	15.75	16	16.50	17.50	18.5	19.5	20.50
AWCBT-400	400	36	99	24	24	24	25	26	27	28	29
AWCBT-500	500	42	90	17.50	17.75	18	18.5	19.50	20.5	21.5	22.50
AWCBT-850	850	54	96	21	21.25	21.50	22	23	24	25	26
AWCBT-1040	1040	60	96	22.75	23	23.25	23.75	24.75	25.75	26.75	27.75

<u>DESCRIPTION:</u> American Wheatley ASME Chilled Water Buffer Tanks are designed for chilled water systems with insufficient water volume capacity, in relation to the chiller capacity. Relatively low water volume systems require additional "buffer" capacity for the system to eliminate problems such as excessive chiller cycling, poor temperature control, and erratic system operation. The properly sized American Wheatley CBT tank adds the necessary volume to "buffer" the system.

TYPICAL SPECIFICATIONS Furnish and install as shown on plans, an ASME Chilled Water Buffer Tank as manufactured by American Wheatley HVAC Products. The tank shall in corporate a baffle to promote tank water storage temperature stratification. The system water connections must be ____ inch (NPT/flanged/grooved).

JOB NAME	
CONTRACTORCONTRACTOR P.O. NO.	

ITEMS	QUANTITY



1005 E. Houston Broken Arrow, OK 74012 Toll Free: 866-204-5229 PH: 918-317-0401 FAX: 918-317-0407

www.wheatleyhvac.com e-mail: sales@globalflowproducts.com