



# LABORATORY FAUCET - DOUBLE


## Z826B1

TAG \_\_\_\_\_



### Engineering Specifications: Zurn AquaSpec® Z826B1

Polished chrome-plated double laboratory faucet with integral shank, quarter turn ceramic disc cartridges and a 5-3/8" [137mm] centerline rigid or swing gooseneck spout. Unit is furnished with a 2.2 GPM [8.3 L] pressure compensating aerator (complying with ANSI A112.18.1 Standard for flow), 2-1/2" [64mm] vandal-resistant color-coded metal lever handles, mounting hardware and stainless steel flex connection hoses.



Note: All dimensions are for reference only. Do not use for pre-plumbing.

### OPTIONAL ACCESSORIES

Suffix	Description
—AR	Anti-Rotation Pins
—CST	Copper Supply Tubes
—FC	2.0 GPM [7.6 L] Laminar Flow Control in Base of Spout
—G	1-1/4" [32mm] Grid Strainer Drain
—HCT	Hot/Cold Text Indexes
—MY	Mixing Yoke Assembly Instead of Copper Supplies
—PT	1-1/4" [32mm] Cast Brass P-Trap with a 7-1/2" [191mm] Long 17-Gauge Wall Bend
—140	Restricted 140° Swing Spout
—2F	2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Aerator
—3F	0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Aerator
—4F	2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Laminar Flow
—5F	2.0 GPM [7.6 L] Female Spray Outlet
—6F	Female Serrated Nozzle Outlet
—7F	1.0 GPM [3.8 L] Pressure Compensating Female Spray Outlet
—16F	1.0 GPM [3.8 L] Vandal Resistant Pressure Compensating Female Spray Outlet
—17F	1.5 GPM [5.7 L] Vandal Resistant Pressure Compensating Female Aerator
—18F	1.5 GPM [5.7 L] Vandal Resistant Pressure Compensating Female Laminar Flow
—18FH	18" [457mm] S.S. Braided Flex Hoses

ZURN INDUSTRIES, INC. ♦ COMMERCIAL BRASS OPERATION ♦ 2640 SOUTH WORK STREET ♦ FALCONER NY 14733

Phone: 1-716-665-1132 ♦ Fax: 1-716-665-1135 ♦ World Wide Web: [www.zurn.com](http://www.zurn.com)

In Canada: ZURN INDUSTRIES LIMITED ♦ 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2 ♦ Phone: 905/405-8272 Fax: 905/405-1292